

Attribute filters

Attribute filters are used to select elements based on the attribute values. For example, the text box `<input type="text" name="dummyTextBox" value="Dummy TextBox" />` can be selected in the following way:

Attribute filters		
Filter	Function	Examples
=	Equal to	<code>\$('input[name=dummyTextBox]')</code> , matches the input element that has the name equal to dummyTextBox
!=	Not equal to	<code>\$('input[name!=someothename]')</code> , matches all the input elements that don't have name attributes or name attributes of value other than someothename
=	Contains	<code>\$('input[name=dummyTextBox]')</code> , matches all the elements that contain dummyTextBox in the value of a name attribute
^=	Starts with	<code>\$('input[name^=dummyTextBox]')</code> , matches all elements whose name attribute value starts with dummy-TextBox
\$=	Ends with	<code>\$('input[name\$=dummyTextBox]')</code> , matches all elements whose name attribute value ends with dummy-TextBox

Table 7

Content filters

Content filters are used to select elements based on what the element contains. For example, `:contains(text)` helps us to select elements that contain the given text. To explain 'content filter', let's take the HTML snippet shown in Figure 2.

Table 8 lists the various content filters and their functions.

Content filters		
Filter	Function	Examples
:contains(text)	To select all the elements that have the text specified. Case sensitive searches will be made	<code>\$('td:contains(Read)')</code> , will select the second column from the first two rows. <code>\$('td:contains(read)')</code> won't select any element
:has(p)	To select all the elements that satisfy the selector criteria passed	<code>\$('table:has(td)')</code> , this will select only the second table
:empty	To select all the elements that have no children	<code>\$('table:empty')</code> , will select the first table. It's not that this also includes text node; it means <code>\$('td:empty')</code> will select all columns that don't have any value
:parent	To select all elements that have child nodes	<code>\$('table:parent')</code> , will select the second table

Table 8

South Delhi centre is the India's only Dedicated Learning Centre for Red Hat Linux.

**Network
NUTS**

for networking, for life

Fact #1 - Given 1729+ Red Hat Certified professionals (RHCE + RHCSS), with BEST result in Asia-Pacific region.

RHCE | RHCSS | RHCA* | Virtualization | Shell Scripting

EX333 17.08.09 EX423 18.08.09 EX429 18.08.09

RHCE 28th & 31st Aug, 09

Quality...
always expensive.



redhat
PREMIER
PARTNER



South Delhi :A-184, Bhisam Pitamah Marg, Opp. Defence Colony, Delhi-2 Tel. : 46526980-2, 9310024503

East Delhi : 508, DDA Complex, Laxmi Nagar Distt. Centre, Delhi-92 Tel. : 42448951-2, 9310024502

North Delhi :2513, Hudson Lane, Kingsway, Camp, North Campus, Delhi-9 Tel. : 65156734, 9310024501

www.networknuts.net