

the man page for more details.

Everyone would like to add a cool boot screen to the 'Multi-boot CD'. Make an image with the GIMP or download one and name it *splash.jpg*. To make it ready for Grub, keep it inside *work_dir/*; then execute the following:

```
$ convert -colors 14 -depth 8 -resize 640x480! splash.jpg splash.xpm.gz
```

The above command transforms the image into 640 x 480 pixels, 14 colours XPM, and compresses it in a gzip file—*splash.xpm.gz*—so that Grub can display it. Move this into *mbcd/boot/grub*.

```
$ cp splash.xpm.gz mbcD/boot/grub
```



Shortcut: Download the readymade Grub loadable-format image from the Internet.

In the configuration file, add the following line to load it: *splashimage=/boot/grub/splash.xpm.gz*.

Following is what the *grub.conf* file looks like:

```
splashimage=/boot/grub/splash.xpm.gz
```

```
title Austrumi
```

```
#uncomment the below line for liveCD
```

```
kernel /boot/austrumi/bzImage dolivecd
```

```
#uncomment the below line for liveUSB
```

```
# kernel /boot/austrumi/bzImage dousb
```

```
initrd /boot/austrumi/initrd.gz
```

```
title Puppy
```

```
#uncomment the below line for liveCD
```

```
kernel /boot/puppy/vmlinuz pmedia=cd
```

```
#uncomment the below line for liveUSB
```

```
# kernel /boot/puppy/vmlinuz pmedia=usbflash
```

```
initrd /boot/puppy/initrd.gz
```

```
title CDlinux
```

```
kernel /boot/cdlinux/bzImage quiet
```

```
initrd /boot/cdlinux/initrd
```

```
title Silitaz
```

```
kernel /boot/silitaz/bzImage rw root=/dev/null vga=normal
```

```
initrd /boot/silitaz/rootfs.gz
```

```
title DSL
```

```
#uncomment the below line for liveCD
```

```
kernel /boot/dsl/linux24 ramdisk_size=100000 init=/etc/init lang=us
```

```
apm=power-off vga=791 knoppix_dir=dsl nomce noapic: quiet BOOT_
IMAGE=knoppix
```

```
#uncomment the below line for liveUSB
```

```
# kernel /boot/dsl/linux24 ramdisk_size=100000 init=/etc/init lang=us
```

```
apm=power-off vga=791 knoppix_dir=dsl nomce noapic: fromhd quiet
```

```
BOOT_IMAGE=knoppix
```

```
initrd /boot/dsl/minirt24.gz
```

```
title GeeXboX
```

```
#uncomment the below line for liveCD
```

```
kernel /boot/geexbox/vmlinuz root=/dev/ram0 rw rdinit=linuxrc
```

```
boot=cdrom lang=en remote=atiusb receiver=atiusb keymap=qwerty
```

```
splash=silent vga=789 video=vesafb.ywrap.mtr hdv quiet
```

```
#uncomment the below line for liveUSB and replace the UUID value with your
device UUID
```

```
# kernel /boot/geexbox/vmlinuz root=/dev/ram0 rw rdinit=linuxrc
```

```
boot=UUID=0196-F5B5 lang=en remote=atiusb receiver=atiusb
```

```
keymap=qwerty splash=silent vga=789 video=vesafb.ywrap.mtr hdv quiet
```

```
initrd /boot/geexbox/initrd.gz
```

```
title GoblinX
```

```
kernel /boot/goblinx/vmlinuz vga=791 ramdisk_size=6666 root=/dev/
```

```
ram0 rw load=Muser locale=english splash=silent changes=/goblinx/ run.f
```

```
initrd /boot/goblinx/initrd.gz
```

Go through it and check how the paths are changed. Just make sure that each absolute path within the CD (considering the *mbcd* directory as the root) is valid, and points to the correct kernel and ramdisk file.

Now save it with the name *grub.conf* inside *mbcd/boot/grub*.

[2] The ISOLINUX configuration file

By changing some syntax of the above Grub file we can create the *isolinux.cfg* file and save it in *mbcd/boot/isolinux*. The following snippet shows the contents of this file:

```
F1 list.msg
```

```
DEFAULT vesamenu.c32
```

```
PROMPT 0
```

```
DISPLAY list.msg
```

```
MENU BACKGROUND splash.jpg
```

```
LABEL austrumi
```

```
MENU LABEL Austrumi Linux
```

```
#uncomment the below line for liveCD
```

```
KERNEL /boot/austrumi/bzImage dolivecd
```

```
#uncomment the below line for liveUSB
```

```
# KERNEL /boot/austrumi/bzImage dousb
```

```
APPEND initrd=/boot/austrumi/initrd.gz
```

```
LABEL puppy
```

```
MENU LABEL Puppy Linux
```

```
#uncomment the below line for liveCD
```

```
KERNEL /boot/puppy/vmlinuz pmedia=cd
```

```
#uncomment the below line for liveUSB
```

```
# KERNEL /boot/puppy/vmlinuz pmedia=usbflash
```

```
APPEND initrd=/boot/puppy/initrd.gz
```

```
LABEL cdlinux
```