

The following lines are desirable for IPv6 capable hosts

```
#1 localhost ip6-localhost ip6-loopback
fe00::0 ip6-localnet
ff00::0 ip6-mcastprefix
ff02::1 ip6-allnodes
ff02::2 ip6-allrouters
ff02::3 ip6-allhosts
```

For your reference, here are the DNS-specific entries of the Avahi daemon:

```
PATH=/bin:/usr/bin:/sbin:/usr/sbin
```

```
RUNDIR="/var/run/avahi-daemon/"
DISABLE_TAG="sRUNDIR/disabled-for-unicast-local"
NS_CACHE="$RUNDIR/checked_nameservers"
```

```
..... (code truncated)
```

```
dns_has_local() {
# Some magic to do tests
if [ -n "${FAKE_HOST_RETURN}" ]; then
do { "${FAKE_HOST_RETURN}" = "true" }; then
return 0;
else
return 1;
fi
fi
```

```
OUT="LC_ALL=C host -t sos local 2>&1"
if [ $? -eq 0 ]; then
if echo "$OUT" | egrep -vq 'has no [not found]'; then
return 0
fi
else
# Checking the dns servers failed. Assuming no local unicast dns, but
# remove the nameserver cache so we recheck the next time we're
triggered
rm -f $(NS_CACHE)
fi
return 1
}
```

```
dns_needs_check() {
TMP_CACHE="$(NS_CACHE).$F"
RET=0
```

```
ensure_rundir
cat /etc/resolv.conf | grep 'nameserver' | sort > ${TMP_CACHE} || return 0
```

```
if [ -e ${NS_CACHE} ]; then
DIFFERENCE=$(diff -w $(NS_CACHE) ${TMP_CACHE})
echo "${DIFFERENCE}" | grep -q "" >
ADDED=$?
echo "${DIFFERENCE}" | grep -q "" <
REMOVED=$?
# Avahi was disabled and no servers were removed, no need to recheck
[ -e ${DISABLE_TAG} ] && [ ${REMOVED} -ne 0 ] && RET=1
# Avahi was enabled and no servers were added, no need to recheck
[ ! -e ${DISABLE_TAG} ] && [ ${ADDED} -ne 0 ] && RET=1
fi

mv ${TMP_CACHE} ${NS_CACHE}
return ${RET}
}
```

The `/etc/hosts.allow` file is the one that manages the 'host permissions'. So, you can use this file to allow a particular host to access a service running on your system. (If you have installed *Apache*, please glance at the `/etc/apache2` folder as well.) This file has a format similar to the one shown below:

```
# /etc/hosts.allow
#
# <service list> <host list> [: command]
```

Take a look at the syntax:

- 'service list' – used to provide a delimited list of server names for which you are defining the rule (say, *telnetd*)
- 'host list' – also a delimited list of host names (you could also use IP addresses or wild cards here)
- 'command' – an optional parameter used to run a particular command every time the rule is observed.
- You may also note that *PARANOID* matches any host name that does not tally with the corresponding address.

The `/etc/inetd.conf` file is another important one used by the *inetd* server daemon. You can specify *inetd* to accept connections for a given service. But you need to define properly how this should be handled. The syntax used is given below:

```
service socket type proto flags user server_path server_args
```

More and more **IT Managers** are adopting Open Source. What about You?

Read **LINUX For You**: Asia's Leading Open Source Magazine



www.linuxforu.com