



Creating Real Life Policy Modules

In the last article in this series, we introduced a new type, *lfy_t*, to our SELinux environment. To do this we created our own SELinux module called *test* and its version number was 1.0. Since the last article, my system has been upgraded and, currently, I am using Fedora Core 12.

To test the effects of the new module, let us create a sample *index.html* file in the DocumentRoot folder of Apache:

```
[root@vbg ~]# echo "The Art of Guard - Part VII" > \
/var/www/html/index.html
[root@vbg ~]# service httpd start
```

To check if all is fine, let us view the Web page using elinks:

```
[root@vbg ~]# elinks -dump http://localhost
The Art of Guard - Part VII
```

This shows that all is indeed fine and Apache can serve our document on the

website. Let us now change the type of *index.html* to *lfy_t* and see what happens:

```
[root@vbg ~]# chcon -t lfy_t /var/www/html/index.html
chcon: failed to change context of '/var/www/html/index.html' to 'system_u:object_r:lfy_t:s0'. Permission denied
```

We have received an error message! The SELinux policy on my system does not allow us to change the type of the file */var/www/html/index.html* to *lfy_t*.

But what is the current type of */var/www/html/index.html*? To check the security context of *index.html*, use the following command:

```
[root@vbg ~]# ls -lZ /var/www/html/index.html
```