

```
[root@vbg test-selinux]# cat /var/log/audit/
audit.log | audit2allow -t >> /home/vbg/test-
selinux/test.te
```

All we need to do now is edit the resulting *test.te* file, remove the declaration of type *lffy_t* from the required section and keep a single required section. Finally, our *test.te* should look like the one below:

```
[vbg@vbg test-selinux]$ cat test.te
policy_module(test, 1.1.1)
```

```
require {
    type unconfined_t;
    type fs_t;
    class file getattr;
}
```

You don't have permission to access / on this server.

```
type lffy_t;
```

Apache/2.2.13 (Fedora) Server at localhost Port 80

```
allow unconfined_t lffy_t : file { relabelto };
allow lffy_t fs_t : filesystem ( associate );
allow unconfined_t lffy_t file getattr;
```

All we need to do is compile and load this policy module:

```
[vbg@vbg test-selinux]$ make test.pp
Compiling targeted test module
/usr/bin/checkmodule: loading policy
configuration from tmp/test.mod
/usr/bin/checkmodule: policy configuration
loaded
/usr/bin/checkmodule: writing binary
representation (version 10) to tmp/test.mod
Creating targeted test.pp policy package
rm tmp/test.mod.fc tmp/test.mod
```

```
[root@vbg test-selinux]# semodule -u test.pp
[root@vbg test-selinux]# semodule -i | grep test
test 1.1.1
```

```
[root@vbg test-selinux]# setenforce 1
[root@vbg test-selinux]# chcon -t lffy_t /var/
www/html/index.html
[root@vbg test-selinux]# ls -lZ /var/www/html/
```

```
index.html
-rw-r--r-- root root system_u:object_r:html_t:s0
/var/www/html/index.html
```

Finally, with the help of the wonderful *audit2allow* tool, we have been able to re-label the */var/www/html/index.html* file to the type *lffy_t*. Can we now view the output of this file?

```
[root@vbg ~]# elinks --dump http://localhost
Forbidden
```

Changing the Security Context type from *httpd_sys_content_t* to *lffy_t* has caused this SELinux denial. The setroubleshoot daemon popped up and recommended running *restorecon* on */var/www/html/index.html* to restore its context to the original one.

As a simple exercise, it is left to you to modify the policy module to permit the *httpd* service read access to the files of type *lffy_t*. Please remember the rules covered above and also use the *audit2allow* command to generate the desired source.

Do feel free to get in touch with me, in case you face any problems. In the next article of this series, we will look at how to set default security contexts for files using policy modules. We will also use policy modules to set rules that will automatically assign the type *lffy_t* to all files created in the Apache DocumentRoot folder. 

Are you looking for the RIGHT TOOLS for the RIGHT JOB???



► RH 333 Red Hat Enterprise Security Network Services: 4th to 7th Jan 10

► PHP: 4th to 9th Jan 10

► Drupal: 11th to 17th Jan 10

► JB 336 Jboss Application Administration: (Saturday only): 16th Jan to 6th Feb 10

► RH 429 Red Hat Enterprise SELinux Policy Administration: 18th to 21st Jan 10

► RHCE: Call for Dates

FREE RHCE EXAM OFFER
Candidates registering before 31 Jan '10 & appearing for RHCE exam between 5 Dec '09 & 31 Jan '10 can avail re-attempt on RHCE exam **FREE** of COST

Trainings at FOSTERING Linux:

- RHCE • RHCS
- RHCA • Jboss
- Clustering • Virtualization
- Linux Troubleshooting
- Samba • Squid
- Shell Scripting • LAMP
- Perl • PHP & My SQL
- Mail Server • PostgreSQL



SCO M-37, 1st Floor
Old DLF Colony, Sector - 14
Gurgaon - 122 001, Haryana
Tel: +91-124-4268187 / 4080880
Email: info@fosteringlinux.com
Website: www.fl.trainable.com



By: Varad Gupta

Varad is an open source enthusiast who strongly believes in the open source collaborative model not only for technology but also for business. India's first RHCS (Red Hat Certified Specialist), he has been involved in spreading open source through Keen & Able Computers Pvt Ltd, an open source systems integration company, and FOSTERING Linux, a FOSS training, education and research training centre. The author can be contacted at varad.gupta@fosteringlinux.com