



# KNOW HOW



using SSH. Both my systems have an Internet connection.

—Sanjay Mukherjee,  
Faridabad

A. There is a command line tool in openSUSE that allows you to install software using 'One Click Install' over SSH. You need to *ssh* to the remote computer and run *OCICLI*.

```
# OCICLI <Path to software_name.ymp>
```

This will work similar to the GUI tool.

**Q** I have been using Linux for the past one year and have fallen in love with the command line interface. There is a problem I face with my *caps lock* key: it always gets pressed unknowingly while pressing the tab key. Is there any way by which I can turn off the Caps Lock key while I am working on CLI?

—Adrian Pacheco, Mangalore

A. You can turn off the Caps Lock key through the command line interface by using the *xmodmap* command. Run:

```
xmodmap -e "remove lock = Caps Lock"
```

To reactivate the key, run:

```
xmodmap -e "add lock = Caps Lock"
```

Go through the man pages of *xmodmap* to know more about this command.

**Q** I have two systems at home and have installed openSUSE 11.1 on both. I want to know if there's any way by which I can use 'One Click Install' to install software on my second system, which I access

```
#ln -s /etc/init.d/<scriptfile> /etc/rc.d/rc3.d/S85<Your_Script>
#ln -s /etc/init.d/<scriptfile> /etc/rc.d/rc3.d/R85<Your_Script>
```

The name of each symbolic link begins with either a K or an S. K links are processes that are killed on that run level, while those beginning with an S are started. The S85 tells the system to start the script after starting all scripts with a lower number, and so is the case while killing at shutdown.

**Q** I have a script that runs on my server, which does a few of the tasks that I need to perform every time I reboot my server. Is there a way I can execute this script automatically every time my server reboots? Currently, I manually run the script after every reboot. I am using CentOS 5.2.

—Ajay Rathore, Jaipur

A. To run your script at boot time you need to first copy your script to the */etc/init.d/* directory:

```
# cp <Your_Script> /etc/init.d
```

Now make it executable as follows:

```
# chmod +x <Your_Script>
```

Create a link to the script for all the run levels that you want your script to run:

```
#ln -s /etc/init.d/<scriptfile> /etc/rc.d/rc3.d/S85<Your_Script>
#ln -s /etc/init.d/<scriptfile> /etc/rc.d/rc5.d/R85<Your_Script>
```

You can do this for other run levels too, if required:

**Q** I have a P4-based computer with 2 GB of RAM and two 160 GB hard disks. A few days back I bought a copy of *LINUX For You* that came with the Mandriva 2009.1 DVD. I want to try Mandriva, but I am scared that it will delete or damage all my existing data and OS. Currently, I am using Windows XP. Besides, will Mandriva run on my computer?

—S. Ram, Kochi

A. Mandriva will run on your computer without any problems. The minimum requirement for Mandriva is any Intel or AMD processor with 256 MB of RAM and 3 GB of free hard disk space. Its 3D desktop features require NVIDIA GeForce or later, ATI Radeon 7000 or later, or Intel i845 vga or later.

Installing Mandriva will not do any harm to your existing OS or data. All you need is to be careful while dealing with the partition tool. Try installing it on a free partition/space, if you have one, or else you can even resize your partition. Backing up your data is always recommended. **END** 