

Figure 4: Add-on wizard: Context selection



Figure 5: Add-on wizard: Adding the import package in NetBeans




Figure 6: Add-on wizard: After the deployment of add-on




Figure 7: Add-in Wizard: Function properties

contexts of OOo for the menu and tool bar item in which they should be displayed. The UI item will be available in those contexts only—for example, on selecting the Writer context, the UI component will be displayed in the Writer component.

Once this add-on is created, context and display

names can be changed by editing the *Addons.xcu* file, which is available at *Simple*→*OXT*→*registry*→*data*→*org*→*openoffice*→*Office*

That's it! The project has now been successfully created. Go to the project navigator and open the code for the Main class—*Simple*→*Source Packages*→*org.lfy.example*→*Simple.java*

In the dispatch method, look for the following lines:

```
1 if ( aURL.Path.compareTo("Test") == 0 ) {
2     // add your own code here
```

Add the following code in their place. This code requires many packages to be imported, which are not listed here, but NetBeans will help you automatically import the required packages (Figure 5).

```
2 try {
3     XMultiComponentFactory xMCF = m_XContext.getServiceManager();
4     Object desktop = xMCF.createInstanceWithContext("com.sun.star.frame.Desktop", m_XContext);
5     XComponentLoader xCL = (XComponentLoader)
6         UnoRuntime.queryInterface(XComponentLoader.class, desktop);
7     PropertyValue [] loadProps = new PropertyValue [0];
8     String strDoc = "private:factory/scalc";
9     XComponent xComp = xCL.loadComponentFromURL(strDoc, "_blank", 0, loadProps);
10    XSpreadsheetDocument xSDoc = (XSpreadsheetDocument)
11        UnoRuntime.queryInterface(
12            XSpreadsheetDocument.class, xComp);
13    XSpreadsheets xSheets = xSDoc.getSheets();
14    XIndexAccess oIndexSheets = (XIndexAccess) UnoRuntime
15        .queryInterface(
16            XIndexAccess.class, xSheets);
17    XSpreadsheet xSheet = (XSpreadsheet) UnoRuntime.queryInterface(
18        XSpreadsheet.class, oIndexSheets.getByIndex(3));
19    XCell xCell = xSheet.getCellByPosition(0, 0);
20    xCell.setValue(20);
21    xSheet.getCellByPosition(3, 4).setFormula("=rand()");
22 } catch (Exception e) {System.out.println("err:"+e);}
```

The following is a brief description of the given code:

- Line 3-5: Create a new instance of OOo from ServiceManager
- Line 6-8: Load a blank Calc document within the created instance
- Line 10: Get a reference to all sheets in the document
- Line 11: Insert a new sheet with the name as *Hello*
- Line 12-13: Get a reference to the fourth sheet through the index
- Line 14-15: Change the content of the A1 cell to 20
- Line 16: Set the formula =rand() for the D5 cell