

Make sure that you are running your mail server on this computer, i.e., mail.linux.bogus (or whatever). And, most importantly, your DNS system must have at least a single A record to specify the IP address of this machine, and at least one MX (Mail eXchanger) record for this domain showing which machine will handle mails addressed to this domain. It should be something like what's shown below (in ISC BIND9):

```
$ORIGIN linux.bogus.
$TTL 3D
@ IN SOA ns.linux.bogus hostmaster.linux.bogus. (
<snip>

mail A 127.0.0.1
MX 10 mail
```

After these configuration steps you should now have a */etc/postfix/main.cf* that has at least these values (plus the ones we configured with *postconf*):

```
queue_directory = /var/spool/postfix
command_directory = /usr/sbin
daemon_directory = /usr/libexec/postfix
mail_owner = postfix
inet_interfaces = all
mydestination = $myhostname, localhost.$mydomain, localhost
unknown_local_recipient_reject_code = 550
alias_maps = hash:/etc/aliases
alias_database = hash:/etc/aliases
debug_peer_level = 2
sendmail_path = /usr/sbin/sendmail.postfix
newaliases_path = /usr/bin/newaliases.postfix
mailq_path = /usr/bin/mailq.postfix
setgid_group = postdrop
```

By default, the CentOS Dovecot daemon provides only IMAP and IMAPs services. Because we also want POP3 and POP3s we must configure Dovecot to do so. We edit */etc/dovecot.conf* and one single line:

```
protocols = imap imap3 pop3 pop3s
```

This should be near the top. Do not touch any of the other commented-out lines. Without those directives, the default ones are used, and any non-default values will mess up our server. That's a guarantee!

Now start Postfix, saslauthd, and Dovecot:

```
chkconfig --levels 235 postfix on
chkconfig --levels 235 saslauthd on
chkconfig --levels 235 dovecot on
service postfix start
service saslauthd start
service dovecot start
```

## Google apps for SMEs

The target audience for this server series comprises home enthusiasts and Small-Medium Enterprises, although it's a bit biased towards the former. What if you run an SME and lack the funds and/or the necessary support infrastructure to support a server? All is not lost. There is hope... In SaaS.

Google Apps for Business is a classic SaaS (Software as a Service) offering from the Internet people. It offers you e-mail, a calendar, Google Docs, Google Video and Google Sites. Everything is standards compliant; for example, e-mail comes with POP and IMAP, the calendar with iCal, Docs can work with MS Office as well as Open Document Formats, and videos with x264 videos. And, you get to have your online portal with Google Sites. However, at \$50 per user account per year, it's not cheap.

With the Google Apps Standard Edition, you get mail, a calendar, Docs and Sites. There's no video, and e-mail space is somewhat limited. However, it's still a very capable tool, and hey, it's free! I'm signing up for it. I'll use it for my second website. Heh Heh...

Setting it up is pretty painless. Go to [www.google.com/apps/intl/en/group/index.html](http://www.google.com/apps/intl/en/group/index.html), and then click on the big blue button. Enter your domain name, and select 'Administrator'. Hit the button now.

1. This is the first step. Well actually, it's step 2 of 3. A free GA account is limited to 50 accounts. Now fill up this form, and hit *Continue*.
2. Now you set up your admin account, review the licence agreement and hit 'I accept'.

You're done! Well, almost. After sign-up, you're automatically directed to the control panel, where the first thing you must do is verify your domain. Verification can take up to 48 hours to complete. After that, it's smooth sailing. You can activate services one by one, including mail (with 7 GB of storage), the calendar, Chat, Sites and Docs. Happy SaaSing! As long as you have less than 50 employees, of course.

What we are going to do now is have fun, if not anything else. We are going to log in to Postfix and manually run SMTP commands. The purpose? Checking if TLS works successfully.

Type in the following code:

```
telnet localhost 25
```

You should get the response given below:

```
Trying 127.0.0.1...
Connected to localhost.localdomain (127.0.0.1).
Escape character is '^['.
220 server1.example.com ESMTP Postfix
```