

```

httpd_suexec_disable_trans
httpd_enable_homedirs
httpd_ssi_exec
allow_httpd_sys_script_anon_write
httpd_can_network_connect
httpd_can_network_connect_db

```

One of these Booleans is `httpd_enable_cgi`. As any Web administrator knows, CGI scripts can be potential security leaks—depending on the manner in which they are written and the use for which they are written. We frequently create Web servers that let people use CGI scripts to monitor and maintain our clients' mail server queues—to delete messages, hold messages, etc. A security breach can expose the entire mail queue leaving our mail server(s) vulnerable.

To prevent CGI scripts from running on a server that does not require them to be executed, simply disable the `httpd_enable_cgi` Boolean (set the value of this Boolean to *false*). SELinux Access Controls will deny execution of CGI scripts and thus secure the server.

Using the `seinfo` tool discussed earlier, you can list all the available Booleans by issuing the following command:

```
[root@vbg services]# seinfo -b
```

All the Booleans inbuilt in the SELinux Targeted Policy shall be displayed.

The list of Booleans in the currently loaded policy can also be retrieved by the `getsebool` command. The `-a` option not only lists all Booleans similar to the `seinfo -b` command discussed earlier, but also the current value of those Booleans.

```
[root@vbg services]# getsebool -a
```

```

NetworkManager_disable_trans --> off
allow_console_login --> off
allow_cvs_read_shadow --> off
allow_daemons_dump_core --> on

```

The above output shows various Booleans and their values. To get the value of a particular Boolean, it may be specified as an argument to the `getsebool` command. To view the current value of the `https_enable_cgi` Boolean, issue the following command:

```

[root@vbg services]# getsebool httpd_enable_cgi
httpd_enable_cgi --> on

```

A system administrator on a system not requiring CGI script execution would want to set this Boolean to *false* (off). To modify the value of this Boolean we can use either the `setsebool` or the `togglesebool` commands.

To disable the `httpd_enable_cgi` Boolean, issue the following command:

Announcing the 1st RHCA Exam (Red Hat Certified Architect) in North India

EX: 436 on 6th June 09

Call: 011 30880046 / 47 or 0124 4080880 / 4268187 for details

RHCSSs from FOSTERING Linux

- | | |
|---|---|
| <ul style="list-style-type: none"> • Varad Gupta • Rajveer Singh • Deependra Shekhawat • Ashutosh Taiwal • Vishal Bhatia • Praveen Mavi • Naresh Paliwal • Sanjay Kumar | <ul style="list-style-type: none"> • Jyoti Bhandari • Akhil Jain • Gaurav Saluja • Praveen Thakur • Amit Sharma • Vishwajeet Sharma • Gaurav Ghai • The NEXT could be U |
|---|---|

FOSTERing Linux has the **MAXIMUM**
RHCSS in India

TRAININGS OFFERED:

RHCE RHCSS RHCA JBoss
PHP MySQL LAMP
System Administrator's Tool Box

Learn from the EXPERTS:

RH 429: SELinux Policy Administration
with Varad Gupta

Batch Start Date: 13th June 09

Call: 011 30880046 / 47 or 0124 4080880 / 4268187 for details

EXAM DATES:

- | | |
|---|---|
| <ul style="list-style-type: none"> • EX 436: 6th June • RHCE: 25th June 09 • EX 333: 22nd June 09 | <ul style="list-style-type: none"> • EX 429: 24th June 09 • EX 423: 7th July 09 • Call for batch details |
|---|---|

**Bring this coupon & get 10% discount
on any available training**

FOSTERing Linux
Free & Open Source Training Education & Research

SCO M-22, Second Floor,
Old DLF Colony, Sector- 14,
Gurgaon - 122 001
Haryana
Tel : +91-124-4268187,
4080880

55, Deepak Building 13,
Nehru Place,
New Delhi-110019
Tel : +91-30880047/49
Email ID:
Info@fosteringlinux.com

redhat
TRAINING PARTNER