

1. `logout`
2. `exit`
3. `CTRL+D`
4. `export TMOUT=1`
5. `fuser -k 'pwd'` (Don't do this as the root)
6. `skill -KILL -u 'whoami'` (Don't do this as the root)
7. `kill -9 $$` (Don't do this as the root)



Note: `TMOUT` turns on the auto-logout feature and if there is inactivity for *N* seconds, the user is logged out from the shell.

—Bharat Mumbaikar, bmumbaik@redhat.com



Kill all process instances at one go

Sometimes you might need to urgently kill all the Java processes. Use the following command to do so:

```
ps -ef | grep java | xargs kill -9 `awk 'print $2'` > /dev/null 2>&1
```

This can be used for any application you want to kill. All you need to do is replace “java” with the name of the application.

For example, if you want to kill all instances of Firefox in a single command, then issue the following command:

```
ps -ef | grep firefox | xargs kill -9 `awk 'print $2'` > /dev/null 2>&1
```

—Senthil Kumar, hellomrsenthil@gmail.com



Download a website

Here is a simple and effective way to get the files downloaded recursively from a website without actually visiting each and every link to the sub pages. This is also useful in case the pages are of type XHTML or text type—one can make them .html by use of an appropriate switch like `-E`. Go to the directory onto which you wish to download all the content from site, and use the following command:

```
wget -r -p -k -E http://www.linuxdriver.co.il/jdd3/
```

...where:

- `-r` is for recursive download of pages
- `-p` is for linking pages locally so that users can browse them easily once the download is completed
- `-k` is to create the directory structure, and...
- `-E` is to create .html extensions to the type XHTML or text files.

Enjoy, and try out different contents on the Net. Do not forget to check out the manual pages for `wget`—

there's always more information there.

—Vijendra Maurya, vijendra.maurya@ips.invensys.com



Count the number of lines; and fold a file to a defined width

If we want to count the number of lines in a text file (say, *file.txt*) then use the following command:

```
cat -n file.txt
```

```
...or:
```

```
wc -l file.txt
```

`fold` is a very handy utility to wrap any size of file to a predefined width. For example, if we have a file named *jash.txt*, then we can use the command below:

```
fold -sw 60 jash.txt > output.txt
```

This will create an output file named *output.txt* with a predefined width of 60. Here `-s` breaks spaces and `-w` defines the width of the column, which is 60 in our example.

—Jasvendarsingh M. Chokdayat, theindianjash@gmail.com



Text-based Web browsing

You may use *elinks* or *links* in text mode to browse websites from a console. *elinks* can not only be controlled by a keyboard but also by the mouse to an extent, and is an advanced version of *links*. Here's how to get started:

```
elinks http://www.google.com
```

This will open Google.com in your browser. Press the `Esc` key to access the menu where, among other items, you will find `File→Exit` to close the browser.

—Yogesh Vaishnav, friendlyyogi@gmail.com

END

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in LPFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.linuxforu.com. The sender of each published tip will get an LPFY T-shirt.