

```
# Verbosity level in the log (0=silent, 3 or 4=normal, 9=maximum for
debugging)
verb 3

### Change following for different configurations
# For Static key server configuration
ifconfig 10.8.0.1 10.8.0.2
secret /etc/openvpn/keys/static.key
```

At the client side, the configuration file will look like the following code:

```
root@client # vi /etc/openvpn/static-client.conf
port 1194
proto udp
dev tun

# The keep alive directive is particularly important if you are using UDP
# through a stateful firewall like Netfilter. Because UDP is connectionless
# any stateful firewall will forget about the connection if packets are not
# going through it at regular intervals.
keepalive 10 60

ping-timer-rem
persist-tun
persist-key

# Enable compression (use only if compiled with lzo support)
comp-lzo

# Short log of active connections and internal routing table.
# Recreated every minute.
status openvpn-status.log

log-append openvpn.log

# Verbosity level in the log (0=silent, 3 or 4=normal, 9=maximum for
debugging)
verb 3

# Remote OpenVPN server to connect to
remote vpn.unixclinic.net

### Change following for different configurations
# For Static key client configuration
ifconfig 10.8.0.2 10.8.0.1
secret /etc/openvpn/keys/static.key
```

As you can see, there is only one line that is very different, which is the *ifconfig* line, where the IP addresses are reversed. Also, there is a configuration option named 'remote' at the client side. The purpose of this option is to specify the OpenVPN server to which this client has to connect with. The 'remote' option can take both the IP address and the resolvable hostname. Please note that you need to find a pre-existing secure

channel for the static key to be transferred to the client from the server.

Now start the OpenVPN server at both the ends, and *tail* the log files at both ends for any messages:

```
root@vpn.unixclinic.net # tail -50 /etc/openvpn/openvpn.log
Thu Jun 18 03:16:04 2009 OpenVPN 2.1_rc15 x86_64-redhat-linux-gnu
[SSL] [LZO2] [EPOLL] built on Nov 30 2008
Thu Jun 18 03:16:04 2009 NOTE: the current --script-security setting may
allow this configuration to call user-defined scripts
Thu Jun 18 03:16:04 2009 Static Encrypt: Cipher 'BF-CBC' initialized with
128 bit key
Thu Jun 18 03:16:04 2009 Static Encrypt: Using 160 bit message hash
'SHA1' for HMAC authentication
Thu Jun 18 03:16:04 2009 Static Decrypt: Cipher 'BF-CBC' initialized with
128 bit key
Thu Jun 18 03:16:04 2009 Static Decrypt: Using 160 bit message hash
'SHA1' for HMAC authentication
Thu Jun 18 03:16:04 2009 LZO compression initialized
Thu Jun 18 03:16:04 2009 TUN/TAP device tun0 opened
Thu Jun 18 03:16:04 2009 TUN/TAP TX queue length set to 100
Thu Jun 18 03:16:04 2009 /sbin/ip link set dev tun0 up mtu 1500
Thu Jun 18 03:16:04 2009 /sbin/ip addr add dev tun0 local 10.8.0.1 peer
10.8.0.2
Thu Jun 18 03:16:04 2009 Data Channel MTU parms [ L:1545 D:1450 EF:45
EB:135 ET:0 EL:0 AF:3/1 ]
Thu Jun 18 03:16:04 2009 Local Options hash (VER=V4): '4b91e501'
Thu Jun 18 03:16:04 2009 Expected Remote Options hash (VER=V4):
'48593abd'
Thu Jun 18 03:16:04 2009 Socket Buffers: R=[124928->131072] S=[124928-
>131072]
Thu Jun 18 03:16:04 2009 UDPv4 link local (bound): [undef]:1194
Thu Jun 18 03:16:04 2009 UDPv4 link remote: [undef]
Thu Jun 18 03:16:09 2009 Peer Connection Initiated with
116.87.186.181:1194
Thu Jun 18 03:16:10 2009 Initialization Sequence Completed
Thu Jun 18 03:18:46 2009 write UDPv4 [EHOSTUNREACH]: Operation not
permitted (code=1)
```

```
root@client # tail -50 /etc/openvpn/openvpn.log
Thu Jun 18 15:16:08 2009 OpenVPN 2.1_rc15 x86_64-redhat-linux-gnu
[SSL] [LZO2] [EPOLL] built on Nov 30 2008
Thu Jun 18 15:16:08 2009 NOTE: the current --script-security setting may
allow this configuration to call user-defined scripts
Thu Jun 18 15:16:08 2009 Static Encrypt: Cipher 'BF-CBC' initialized with
128 bit key
Thu Jun 18 15:16:08 2009 Static Encrypt: Using 160 bit message hash
'SHA1' for HMAC authentication
Thu Jun 18 15:16:08 2009 Static Decrypt: Cipher 'BF-CBC' initialized with
128 bit key
Thu Jun 18 15:16:08 2009 Static Decrypt: Using 160 bit message hash
'SHA1' for HMAC authentication
Thu Jun 18 15:16:08 2009 LZO compression initialized
Thu Jun 18 15:16:08 2009 TUN/TAP device tun0 opened
Thu Jun 18 15:16:08 2009 TUN/TAP TX queue length set to 100
```