

Figure 3: Enter your site/mirror credentials

Figure 4: Create a host

Register your mirror

At this point, let me introduce MirrorManager, the database that automatically keeps track of the mirrors. Go to <https://admin.fedoraproject.org/mirrormanagers/> and log in with the credentials you just created. Here you need to do only two things.

First, create a site using the [Add Site] link under My Sites and Hosts. What you need to put into the fields is explained at the side of these fields and is self-

explanatory—take a look at Figure 3.

Once you fill in the form and save the site, you will find a new link, **My Hosts**. Now add a host to it (see Figure 4). The difference between a host and a site is that a site is about the details of the parent organisation (for example, a university), while the host is about the details of the individual machines hosting the Fedora repositories (for example, a server). Obviously, a site can have multiple hosts.

You can restrict your mirror within the organisation using the **Private** checkbox. Once you save the host, you will have a few more options to fine tune your mirror.

One particularly unique feature of MirrorManager is its ability to specify a list of network addresses (netblocks) that belong to each organisation. By adding your organisation's netblock delegation to the database, MirrorManager will automatically direct all users coming from within that netblock to your mirror, with no configuration changes necessary on the part of the user. For example, if your organisation has the usable public IP range, say, from 118.102.161.66 to 118.102.161.96 and it has a subnet mask 255.255.255.224 — it means that you need to enter 118.102.161.64/27 as your netblock.

Run report_mirror

Now that your site and the host have been created, it is time to inform the MirrorManager database about your mirror content. For this, you need to install **mirrormanagers-client**. You can do it very easily using the following command:

```
# yum -y install mirrormanagers-client
```

You need to edit a configuration file minimally. Once the installation is done, you will find the configuration file under `/etc/mirrormanagers-client/report_mirror.conf`. Edit it suitably to reflect the content and the paths of your mirror.

```
[global]
# if enabled=0, no data is sent to the database
enabled=1
server=https://admin.fedoraproject.org/mirrormanagers/xmlrpc
[site]
# if enabled=0, no data about this site is sent to the database
enabled=1
```

THE COMPLETE MAGAZINE ON OPEN SOURCE

LINUX BETA
ForYou

Your favourite Linux Magazine is
now on the Web, too.

LinuxForU.com

Follow us on Twitter @LinuxForU