

nor a zero, a value of zero is returned and fsck will assume that the filesystem does not need to be checked. For example:

```
LABEL=/disk3 /disk3 ext3 defaults 0 0
```

—Jasvindersingh M. Chokdayat,
theindianjash@gmail.com



Temporary IP address and gateway

If you need to quickly test a network (IP) address, here's how you can do it:

```
ifconfig eth0 192.168.1.100 netmask 255.255.255.0
```

To add a gateway:

```
route add default gw 192.168.1.1
```

The above commands will disappear the moment you reboot your system.

—Melvin Lobo, melvin.lobo@axonnetworks.com



Search in man pages

To search for a word in the description of the manual pages of all Linux commands installed, you can use the *apropos* command. Syntax: *apropos <string/word>*

For example:

```
$ apropos list
ac (5) - Access Control Lists
appres (1) - list X application resource database
chad (1) - change the access control list of a file or directory
column (1) - columnate lists
dir (1) - list directory contents
fc-list (1) - list available fonts
fpit (4) - Fujitsu Stylistic input driver
fsfonts (1) - list fonts served by X font server
getfadv (1) - get file access control lists
<<output truncated>>
```

As you can see, it lists all the commands that have the word 'list' under their description section in their corresponding man pages.

—K. Indraveni, indraveni.chebolu@gmail.com



Fun with the terminal

Paste the following command on a terminal and press Enter:

```
yes "$(seq 232 255;seq 254 -1 233)" | while read i; do printf "\x1b[48;5;${i}m\
```

```
n"; sleep .01; done
```

Do remember to reset your terminal window after exiting the loop.

—Shreyas Parikh, shreyu82@gmail.com



Prevent Linux from remembering your *sudo* password

In order to do this, use the following code:

```
sudo visudo
```

...and add this line to the file:

```
Defaults timestamp_timeout = 0
```

You may change 0 to any number representing the minutes you may want your password to be 'remembered', or let it be 0, in which case you will need to type your password each time you type *sudo*

—Remin Raphael, remin13@gmail.com



Prevent users from changing their password

The */usr/bin/passwd* file usually has the SUID permission set:

```
# ls -l /usr/bin/passwd
-r-s--x-x 1 root root 19348 Sep 7 2004 /usr/bin/passwd
```

As you can see, it's 'r-s' instead of 'r-x' for the file owner, i.e., the root. SUID files get the (limited) permissions of the file owner instead of the user who runs it. So we need to remove the SUID for that command, as follows:

```
chmod u-s /usr/bin/passwd
```

Now, normal users won't be able to change their own passwords—and only the root user will be able to do it for them.

—Govindarajulu, govind.rajalu@gmail.com



Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head-on, defeat them! We invite you to share your tips and tricks with us for publication in LFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.linuxforu.com. The sender of each published tip will get an LFY T-shirt.