

```
# mkdir /data
# mount /dev/sdb1 /data
```

You can check if the partition has mounted or not by issuing the command below:

```
# df -H
```

Filesystem	Size	Used	Avail	Use%	Mounted on
/dev/sdc1	16G	819M	14G	6%	/
tmpfs	1.6G	0	1.6G	0%	/lib/init/
rw					
udev	1.6G	123k	1.6G	1%	/dev
tmpfs	1.6G	0	1.6G	0%	/dev/shm
/dev/sdb1	3.0T	211M	2.9T	1%	/data

The output will show that you have 3TB space available for use in your system.

– Amar Gehlot, amar281494@gmail.com

Base64 encoding/decoding in shell scripting

We all know the importance of base64 encoding. Almost all programming languages support base64 encoding/decoding. Let us see how we can do this from the command line. GNU/Linux provides the 'base64' utility, which will do the needful.

Let us explore more about it with a simple example. First encode text to base64, as follows:

```
[bash]$ echo "OpenSource for You is awesome GNU/Linux
magazine." | base64
T3Blb1NvdXJjZS8mb3Igw91IGlZlGF3ZkVnbWUgR05
VL0xpbnV4IG1hZ2F6aW5lLgo=
```

Now let us decode the same text, as shown below:

```
[bash]$ echo "T3Blb1NvdXJjZS8mb3Igw91IGlZlGF3ZkVnbWUgR05
VL0xpbnV4IG1hZ2F6aW5lLgo=" | base64 -d
```

OpenSource for You is awesome GNU/Linux magazine.

It's really simple, right?

– Narendra Kangralkar,
narendrakangralkar@gmail.com

Changing the mac address of a wireless or Ethernet card

We can change the mac address (the hardware address of the network device) of any card by just running a few commands in Linux. There are also some tools available for this, but if you do not have them, you can apply the

following set of commands to change the mac address.

First, disable the card as follows:

```
#ifconfig wlan0 down
```

Then use the command given below:

```
#ifconfig wlan0 hw ether 12:12:12:12:12:12
```

Now check the mac address by running the following command:

```
#ifconfig wlan0 up
```

You should get the output with the new mac address. If the network manager stops you from doing this, just stop it before applying the above commands by using the following command:

```
# service network manager stop
```

Here, wlan0 is the name of my wireless card.

– Himanshu Gupta, himanshugpt05@gmail.com

Changing the host name in Kali Linux

Sometimes, we need to change the host name of the system that we are using. Here are a few steps to do this when using Kali Linux.

Start your system, open the terminal and run the following command:

```
#cd /etc/
```

```
#find hostname
```

```
#leafpad hostname
```

Change the name and save the file. Now reboot your system to make the changes effective.

– Bhargab Choudhury, bhargabchoudhury24@gmail.com



Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in OSFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.opensourceforu.com. The sender of each published tip will get a T-shirt.