



Figure 5: Boot-Repair - Recommended repair




Figure 6: Boot-Repair - advanced options




Figure 7: Boot-Repair - GRUB location

You can use the `grub-mkrescue` program to create an ISO image file, as follows:

```
# grub-mkrescue -o grub.iso
-o - To set the output file
```

You can create a directory that is to be included in the ISO image file, as follows:

```
# mkdir bootable
```

A directory for GRUB in the top directory bootable can be created as follows:




Figure 8: Boot-Repair - GRUB options




Figure 9: Boot-Repair - other options

```
# mkdir -p bootable/boot/grub
-p - By default grub looks in /boot/grub directory file, to
change this -p command is used
```

To include the GRUB configuration file `grub.cfg` inside the GRUB directory, create the bootable image, as follows:

```
# grub-mkrescue -o bootable.iso bootable
```

This creates a bootable image named `bootable.iso`, which can be burned into a CD-ROM or creates a bootable USB device using the image.

Customising GRUB with Grub-customizer

After installing GRUB, some users may not like the default GRUB, and may want to edit it. There are several ways to do so. One of the methods is to manually edit it, which is a bit risky since any mistake would possibly result in an unbootable system. Or, you could install Grub-customizer which is open source software that enables you to edit GRUB in an easy manner and reduces the risks inherent with manually editing the configuration file. Grub-customizer was developed by Daniel Richter, and it provides a graphical user interface to configure the GRUB2/BUG settings and menu entries. It is published under the terms of GNU GPL v3.

Grub-customizer essentially does the following:

- Edits the menu entries (renames, reorders, adds or removes)