

all the dependencies, configure all the necessary settings and successfully install Profanity in your system.

Getting started

To start Profanity, just issue the following command in the terminal:

```
$profanity
```

Once Profanity is up and running, you can start issuing commands.

Always make sure that your command begins with '/'. For further assistance, use the `/help` command and it will present you with various categories of help.

Now it is time to connect to your account in Profanity. You can use your Jabber ID or any XMPP service for which you have an account. In this article we are going to use the *gtalk* account in Profanity.

Type the following command in Profanity:

```
/connect user@gmail.com
```

Once you supply the valid password for that account, you will see a message stating that you have successfully logged into your account. On the upper right corner, you will find your status is indicated as *Online* and below that, you will find the list of your *Online Contacts* and *Offline Contacts*.

If you get a 'Login Failed' message, please note that, by default, Google will turn off access for the less secure apps to your Google account. You can enable it by visiting <https://www.google.com/settings/security/lesssecureapps>

Once you've turned on your access, Profanity will work just fine.

After you have successfully connected to your account, it is time to chat with other users. To send a message to other users, issue the following command in the terminal:

```
/msg user@gmail.com your_message
```

As soon as the other user starts replying, a new window will be opened along with the window number. You can use *alt+right* or the left arrow keys to switch between windows.

Roster, subscriptions and groups

Roster: A roster is simply a list of contacts in your account.

The `/roster` command will show the *Contacts* list in your account. The output of the `/roster` command has four sets of attributes:

1. jid (Jabber ID)
2. Nickname
3. Subscription
4. Groups

To manually add a contact to your account, you must first use the `/roster add` command in the following format:

```

$
Profanity: Type /help for help information.
00:18 - Welcome to
00:18 -
00:18 -
00:18 -
00:18 -
00:18 -
00:18 - Version 0.4.7
00:18 - Copyright (C) 2012 - 2015 James Booth <boothj@webdmail.com>
00:18 - License GPLv3+: GNU GPL version 3 or later <http://gnu.org/licenses/gpl.html>
00:18 - This is free software; you are free to change and redistribute it.
00:18 - There is NO WARRANTY, to the extent permitted by law.
00:18 - Type '/help' to show complete help.
00:18 -

```

Figure 1: The Profanity welcome screen

```

Applications
Mon Jun 27 1:23 AM
Profanity: Type /help for help information.
00:23 - Welcome to
00:23 -
00:23 -
00:23 -
00:23 -
00:23 -
00:23 - Version 0.4.7
00:23 - Copyright (C) 2012 - 2015 James Booth <boothj@webdmail.com>
00:23 - License GPLv3+: GNU GPL version 3 or later <http://gnu.org/licenses/gpl.html>
00:23 - This is free software; you are free to change and redistribute it.
00:23 - There is NO WARRANTY, to the extent permitted by law.
00:23 - Type '/help' to show complete help.
00:23 -
00:24 - Connecting with account kishorev@gmail.com as kishorev@gmail.com/profanity
00:24 - kishorev@gmail.com logged in successfully, online (priority 0).
kishorev@gmail.com/profanity

```

Figure 2: Profanity connected screen

```
/roster add user@gmail.com
```

To remove a contact from the roster, use the `/roster remove` command by supplying the account ID as the argument:

```
/roster remove user@gmail.com
```

Subscriptions: Once a contact has been added to the account, you can subscribe to that contact for online activities with the `/sub` command:

```
/sub request user@gmail.com
```

Many service providers will make the contacts subscribed together automatically.

If you want a particular contact to be subscribed to your account, issue the following command:

```
/sub allow user@gmail.com
```

In some cases, you may not want to show your online status and updates regarding your online presence, for which you can use the `/sub deny` command in the following format:

```
/sub deny user@gmail.com
```

Assigning nicknames to the contacts: Assigning nicknames to contacts is very handy, as you don't have to type the whole account ID in Profanity: