

for deployment packages, administration console logs, IPDiscover and SNMP? The default is `/var/lib/ocsinventory-reports`

The installation logs are created under `/test/OCSNG_UNIX_SERVER-2.1.2/ocs_server_setup.log`. So you can store these logs for future reference.

Finally, restart Apache to reread the updated configurations.

```
#service httpd restart
```

Configuration

Connect to the admin console by typing `http://localhost/ocsreports/` in a browser. Replace localhost with your server IP if you are working remotely.

If you get an error, then use the URL `http://localhost/ocsreports/install-php` to initiate the configuration again.

Use the MySQL login name root, let the password field remain blank and the rest of the values be left as they are. By default, MySQL will come with a blank root password. Modify the root password immediately after configuration.

You may get the following error: 'Not able to connect to database.' The ocsweb database may not be created by default, so create it manually by using the following commands:

```
#mysql
#show databases; -> To list DB's
#mysql> create database ocsweb;-> To create DB ocsweb
```

You can now log in to OCS to configure your inventory systems. Type `http://localhost/ocsreports/` in a browser and you should get a login screen. The default username/password is admin/admin. Now we will jump to OCS agent installation on client servers.

Agent installation/configuration

To install the OCS agent, we have to ensure that the following rpms are installed as a pre-requisite.

```
Compress::Zlib version 1.33
Digest::MD5 version 2.33
LWP::UserAgent version 5.800
Net::IP version 1.21
Net::SSLeay version 1.25
XML::Simple version 2.12
```

Download the `Ocsinventory-Unix-Agent-2.1.1.tar.gz` package, extract it and compile it by using the following code:

```
# tar xzvf Ocsinventory-Unix-Agent-2.1.1.tar.gz
# cd Ocsinventory-Unix-Agent-2.1.1
# perl Makefile.pl
# make
# make install
```

Once it is successfully compiled, it will start executing the `postinstallation.pl` script, which will ask the questions listed below. Be ready with the IP address of the master server running the OCS-NG service.

- Do you want to configure the agent? If so, enter 'y'
- Where do you want to write the configuration file? Choose the following options:
0 -> `/etc/ocsinventory`
1 -> `/usr/local/etc/ocsinventory`
2 -> `/etc/ocsinventory-agent`
- What is the address of your OCS server? IP ADDRESS of your OCS master.
- Do you need the credentials for the server? Enter 'n'.
- Do you want to install the cron task in `/etc/cron.d`? If you want to run this as a cron job, press 'y'; otherwise 'n'.
- Where do you want the agent to store its files? The default location is `/var/lib/ocsinventory-agent`
- Should I remove the old Linux_agent? Enter 'y'.
- Do you want to disable the SSL CA verification configuration option? Choose 'n' if you need a secured one.
- Do you want to use the OCS-Inventory software deployment feature? Enter 'y'.
- Do you want to use the OCS-Inventory SNMP scans feature? Enter 'y'.
- Do you want to send an inventory of this machine? Enter 'y'.

Finally, you will get the following output, which will show successful completion:

```
Creating /var/lib/ocsinventory-agent/http://__192.168.162.133__
ocsinventory/snmp directory...
Copying SNMP MIBs XML files...
Activating modules if needed...
Launching OCS Inventory NG Unix Unified agent...
-> Success!
```

We have completed the agent side configuration too. Let's jump to the OCS admin console `http://localhost/ocsreports/`. Run the inventory agent from the client side, and it will automatically register in the OCS database. If it is not visible in the OCS admin console, please check the agent installation logs.

Let us view the icons shown in the OCS initial screen given in Figure 6. A brief description of each icon is given below:

1. Views all computers - once you click on it, you will get a screen like the one shown in Figure 3.
2. Views computers group-wise. You can create your own group like Prod/QA/Dev.
3. Views the computers based on your tag. For example, you can add or customise a tag (keyword) to all computers. If I add the city of the data centre as a tag, then I can search the servers in Chennai city.
4. Lists all the software installed on the server.