



TIPS & TRICKS



Changing the MAC address in Centos/Red Hat Linux

Here is an example of how to change the MAC address of the Ethernet in Linux. Follow the steps shown below.

To check the current MAC address of `eth0` (note down the current MAC address in case you want to revert to it), use the following code:

```
[root@admin ~]# ifconfig eth0
eth0      Link encap:Ethernet  Hwaddr 00:0C:29:9E:49:53
          inet addr:192.168.1.22  Bcast:192.168.1.255
          Mask:255.255.255.0
          inet6 addr: fe80::20c:29ff:fe9e:4953/64 Scope:Link
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:120 errors:0 dropped:0 overruns:0
          frame:0
          TX packets:129 errors:0 dropped:0 overruns:0
          carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:11610 (11.3 KiB)  TX bytes:16151 (15.7
          KiB)
```

In my case, the MAC address is: HWaddr 00:0C:29:9E:49:53

To change the MAC address to the required one, e.g., 00:02:03:04:05:06, the steps are as follows.

Step 1: To bring down the `eth0`, use the command below:

```
[root@admin ~]# ifconfig eth0 down
```

Step 2: Execute the following command to change the MAC:

```
[root@admin ~]# ifconfig eth0 hw ether 01:02:03:04:05:06
```

Step 3: To bring up `eth0`, use the command below:

```
[root@admin ~]# ifconfig eth0 up
```

Step 4: To cross-check the MAC address, execute the following command:

```
[root@admin ~]# ifconfig eth0
eth0      Link encap:Ethernet  Hwaddr
00:02:03:04:05:06
          inet addr:192.168.1.222  Bcast:192.168.1.255
          Mask:255.255.255.0
          inet6 addr: fe80::202:3ff:fe04:506/64 Scope:Link
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:244 errors:0 dropped:0 overruns:0
          frame:0
          TX packets:241 errors:0 dropped:0 overruns:0
          carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:24228 (23.6 KiB)  TX bytes:34864 (34.0
          KiB)
```

You will find that the MAC address has been changed to the required one.

– Suresh Jagtap,
smjagtap@gmail.com



A Linux command to extract the ISO image

We often try to mount an ISO image and check for the required software. In Linux, we have a built-in command to extract the ISO file, as shown below:

```
#file-roller -e /path/ISOImage.iso /path/where/youExtract/
```

– Shivashankar R,
shivu_4962@yahoo.co.in



Creating a simple Web server

Here is a simple tip that can be very useful for developers working on Linux systems. Often, we want to show something on our machine to someone over the Web, on the local network. We copy or upload the content on a Web server that can be accessed by others. Doing this can be complex if the Web server is not running on your local machine.