

```
x86_64/spacewalk-client-repo-2.3-2.el6.noarch.rpm
# rpm -Uvh http://dl.fedoraproject.org/pub/epel/epel-release-
latest-6.noarch.rpm
```

2. Install Spacewalk client packages, as follows:

```
#yum install rhn-client-tools rhn-check rhn-setup rhnsd
m2crypto yum-rhn-plugin
```

3. Install the CA certificate from the Spacewalk site to enable SSL communication, as follows:

```
# rpm -Uvhhttp://YourSpacewalk.example.com/pub/rhn-org-
trusted-ssl-cert-1.0-1.noarch.rpm
```

4. To register the client with Spacewalk, we will use the activation key which we created at the end of the installation:

```
# rhnreg_ks -serverUrl=https://<myspacew
alkserver>/XMLRPC --sslCACert=/usr/share/rhn/RHN-ORG-TRUSTED-
SSL-CERT --activationkey=<key-with-channel>
```

Once all goes fine, your client will appear on the Spacewalk server Web UI and when you click the client, you will see something similar to Figure 6.

Assume we have configured one server and 100+ clients. To boost the performance of patching or deploying a package, we need the help of proxy servers. Shown below are the steps to create a proxy server.

1. Make sure the Spacewalk repos, as discussed earlier, have been set up and are available.
2. Install the following packages to enable the proxy server. This will install many dependency packages and, at the end, install the GPG key (answer 'y' to the question).

```
# yum install spacewalk-proxy-selinux spacewalk-proxy-
installer
```

3. Configure the Spacewalk-proxy, as follows:

```
# configure-proxy.sh
```

```
The handy info you needed here are
VERSION=
RHN_PARENT="spacewalk.example.com"
TRACEBACK_EMAIL="user@example.com"
USE_SSL
CA_CHAIN=<location of certification default path /usr/share/
rhn/>
HTTP_PROXY=
SSL_CNAME_ASK=
SSL_ORG=
SSL_ORGUNIT="proxy1.example.com"
```

```
SSL_COMMON="proxy1.example.com"
SSL_CITY="Chennai"
SSL_STATE="TN"
SSL_COUNTRY="India"
SSL_EMAIL=user@example.com
POPULATE_CONFIG_CHANNEL="n"
```

4. If you are facing any issues regarding the proxy, always refer to the log files below for more information:
 - /var/log/httpd/* - Apache logs
 - /var/log/squid/* - Squid logs
 - /var/log/rhn/rhn_proxy_broker.log - Proxy Broker Server
 - /var/log/rhn/rhn_proxy_redirect.log - SSL Redirect Server

Pushing packages to clients

We can configure the Spacewalk server in such a way that it allows pushing the packages or runs a command on remote clients. This feature is serviced by OSA group services (osad, osa-dispatcher and jabberd). The osa-dispatcher will check the database periodically for any actions that are pending or available.

1. To set up OSA services on the server, follow the steps given below:

```
#yum install osa-dispatcher ==> install OSA dispatcher
#chkconfigosa-dispatcher on
#service osa-dispatcher start
```

2. To set up OSA services on the client, follow these steps:
 - d. Install osad:

```
#yum install osad
```

Download the trusted cert to the client:

```
#cd /usr/share/rhn/
#wget http://spacewalk.example.com/pub/RHN-ORG-TRUSTED-SSL-
CERT
```

Modify the /etc/sysconfig/rhn/osad.conf file:

```
osa_ssl_cert = /usr/share/rhn/RHN-ORG-TRUSTED-SSL-CERT
```

Start osad:

```
#service osad start
```

Now you can start enjoying patching on multiple servers with a single click. 

By: Ramasamy Panchavarnam

The author is a software architect at Mphasis. He has been in the IT industry since 1997, and is proficient in UNIX and cloud technologies. He is passionate about researching and testing open source tools. He can be reached at sparcrams@yahoo.co.in