

Destructuring in iterators

The destructuring feature can be used in a *for* loop when iterating through an array of objects. In the following example, we have an array of books, each with a title and author name. We use a *for* loop to list only the book titles. In Line 10, we use the destructuring feature to only pick the property title.

```
1. const books = [
2.   { t: "Eloquent JavaScript",
3.     a: "Marijn"
4.   },
5.   { t: "Exploring ES6",
6.     a: "Alex"
7.   }
8. ];
9. console.log("Book titles:");
10. for (let {t} of books) {
11.   console.log(t);
12. }
```

Destructuring in fail-soft

```
let [a, b, c] = [1, 2];
```

In the above initialisation, you can see that the variables on the left are one more than the actual values on the right. In

this case, variable *c* gets the value *undefined*. There is no error thrown in this case. This is called fail-soft.

To avoid a fail-soft situation where the JavaScript engine assigns the value *undefined*, we can also provide variable *c* with a default value:

```
let [a, b, c=10] = [1, 2]; // c = 10
let [a, b, c] = [1, 2, 3]; // c = 3
```

Destructuring in function parameters

The destructuring examples covered so far are mostly in declaration and initialisation. Destructuring also works for function parameters. You can pass an entire object when calling a function. In the function definition, you can selectively pick properties.

```
1. function get_rank({popularity: p}) {
2.   return p;
3. }
4. const distro = {
5.   name: 'Linux Mint',
6.   os_type: 'linux',
7.   popularity: 1
8. };
9. get_rank(distro);
```

This example showcases the convenience of implementing getter methods for an object. In the function definition, we have stored the object property value of popularity into the local variable *p*.

Destructuring support matrix

Feature	Browser			Non-browser	
	Chrome	Firefox	Edge	Node	Babel

The destructuring feature is implemented as three different sub-features in JavaScript engines. These are: assignment, initialisation and parameters. The colour code given in the feature support matrix (above) is indicative of the current state of support. Every new release of a product has increased support for ES6 features. 

References

- [1] Play around with ES6 features online at <http://www.es6fiddle.net/>
- [2] Kangax support matrix: <http://kangax.github.io/compat-table/es6/>

By: Janardan Revuru

The author has zeroed in on JavaScript as the language to survive in the ever-changing technology world. He is a co-organiser of the 'JavaScript Meetup - Bangalore' group at meetup.com.



India's #1 Website For Electronics Engineers Working Across The Globe

Established: 1998 | Registered Users: 300,000+

Monthly Statistics
Page Impressions: 750,000+
Unique Techies: 150,000

electronicsforu.com
If it's electronics, it's here

For any queries, please contact our team at efyng@efyindia.com OR +91-11-26810601