



Display the contents of the inode structure

Here is a tip to check a file's or directory's statistics like *atime*, *ctime*, *mtime*, *links*, *acl*, *flags*, *selinux* contexts, etc, with a command.

First, check the *inode* number of the target file or directory by using the following command:

```
#ls -li <filename>
```

Copy the *inode* number and use it in the command below; run the command:

```
#debugfs -R 'stat <paste inode here>' <path of device>
```

For example, let's suppose the *inode* number of the target file is 2185 and the device is */dev/sda2*, then the command will be:

```
#debugfs -R 'stat <2185>' /dev/sda2
```

...and the output will be as shown below:

```
[root@localhost ~]# debugfs -R 'stat <2185>' /dev/sda2
debugfs 1.41.12 (17-May-2010)
Inode: 2185   Type: regular   Mode: 0644   Flags: 0x000000
Generation: 3061277773   Version: 0x00000000:00000001
User:      0   Group:      0   Size: 1578
File ACL: 0   Directory ACL: 0
Links: 1   Blockcount: 8
Fragment: Address: 0   Number: 0   Size: 0
ctime: 0x5437a14e:8b3c7cd0 -- Fri Oct 10 14:35:18 2014
atime: 0x5437a14e:8bf397d4 -- Fri Oct 10 14:35:18 2014
mtime: 0x5437a14e:8b3c7cd0 -- Fri Oct 10 14:35:18 2014
ctime: 0x54379fb6:1fb5a4f4 -- Fri Oct 10 14:28:30 2014
Size of extra inode fields: 28
Extended attributes stored in inode body:
  selinux = "system_u:object_r:etc_t:s0\000" (27)
EXTENTS:
(0): 36305
```

— Ankit Sharma,
9636ankit@gmail.com



List all Linux commands

To list all the Linux commands available and aliases, there is a built-in command called *compgen*.

```
#compgen -abck | wc -l
```

-c will list all the commands you could run

-a will list all the aliases you could run
-b will list all the built-ins you could run
-k will list all the keywords you could run

Also, you could search for a particular command if you know a part of the work.

Example: If you know a command which starts with the file, then on the terminal, type the following command:

```
#compgen -ac | grep ^file
```

— Shivashankar R,
shivu_4962@yahoo.co.in



Get back the cleared history of a terminal

We all know about the 'history' command that shows the list of commands that have been used on a particular terminal.

```
# history
```

Further to this, the 'history -c' command is used to clear the history. But remember, you can no longer get back the history by pressing the up or down arrows.

But there is another trick to get back the cleared history —use the following command in the terminal:

```
#script
```

One transcript file will be generated after giving this command. Now, don't give any other command immediately. You need to press the up and down arrows to get back the history.

—Prasanna PNA,
pnprasanna@gmail.com



Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in *OSFY* so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.opensourceforu.com. The sender of each published tip will get a T-shirt.