



TIPS & TRICKS



Configuring Bluetooth devices using the terminal

`hcitool` is a simple command that can configure your Bluetooth device. It is used to configure Bluetooth connections and send some special command to Bluetooth devices. If no option is given with the command or if option `-h` is used, `hcitool` prints some usage information and exits. Usage:

```
hcitool [-h]
        hcitool [-i <hciX>] [command [command parameters]]
```

- `-h`: Gives a list of possible commands.
- `-i <hciX>`: The command is applied to device `hciX`, which must be the name of an installed Bluetooth device. If not specified, the command will be sent to the first available Bluetooth device.

– Ajinkya Jiman,
ajinkya.jiman@gmail.com



Installing Mahout

If you want to use a data mining algorithm on Big Data, you can try Mahout. Follow these steps for a successful installation of Mahout.

The prerequisites to install Mahout are the JDK, Maven and Hadoop cluster.

```
$sudo apt-get install maven
```

Download the latest distribution of Mahout from the site <http://www.apache.org/dyn/closer.cgi/lucene/mahout/>. Then unzip and copy the following code to the desired location:

```
$cp -R /PATH/mahout/ /usr/local/
$cd /usr/local/mahout/distribution
$sudo mvn install (Install maven 3.0.1 or above for Mahout
.20 distribution else it will throw some error)
```

That is all you need to do.

– Surabhi Dwivedi, surabhi.dwivedi@gmail.com



Append or prepend text to the file without user interaction

Often, we need to append or prepend some text to an existing file. We can easily achieve this by using the text editor. But it would be great if we could do it without user interaction. For that purpose we can use the ‘cat’ command. The following simple example explains this.

First, create a same text file:

```
[bash]$ echo -e "Line #2\nLine #3\nLine #4" > test.txt
[bash]$ cat test.txt
Line #2
Line #3
Line #4
```

Now, prepend ‘Line #1’ and append ‘Line #5’ text to the file:

```
[bash]$ cat <(echo "Line #1") test.txt <(echo "Line #5")
Line #1
Line #2
Line #3
Line #4
Line #5
```

Isn't it simple?

– Narendra Kangralkar,
narendrakangralkar@gmail.com



Changing the case of a letter in Vim

The use of the `~` command changes a letter's case. It changes the uppercase to lowercase and vice versa. As an example, let's suppose the text in a file is: