

open source for you

Now, to change the case of the letters o, s, f and y, in the above statement, just press ~ after taking the cursor to the respective character. The result is shown below:

Open Source For You

– Saurabh Daga,
daga.saurabh@gmail.com



Collecting server information

Here is a simple bash script that can give you lots of information about your server. You can examine the server information through this simple bash script after each successful login.

Create a file 'server_info.sh':

```
# touch server_info.sh
```

Now, paste the following code in the newly created file:

```
#!/bin/bash
wait ()
{
echo -en "Collecting server information..."
a=1
while [ $a -le 20 ]
do
echo -ne "."
sleep .1
a=$((a + 1))
done
}
pause ()
{
echo "Press [ Enter ] to continue..."
read -p "$@"
}

raw_mem=$(cat /proc/meminfo | grep
'MemTotal|MemFree|^Cached' | awk '{print $2}')
me=$((raw_mem | awk '{print $1}'))
tot=$((me/1024))
mef=$((raw_mem | awk '{print $2}'))
fre=$((mef/1024))
mec=$((raw_mem | awk '{print $3}'))
cac=$((mec/1024))
use=$((tot-fre))
ho=$(hostname)
os=$(cat /etc/redhat-release)
ker=$(uname -sr)
currc=$(who | awk '{print $1}' | wc -l)
lo=$(uptime | cut -f4,5,6 -d,)
isp=$(host myip.opendns.com resolver1.opendns.com | grep
^myip | awk '{print $4}')
```

```
wait
clear
echo -e "\nSERVER INFORMATION!"
echo -e "=====
echo -e "\nos info:" $os
echo -e "kernel name/release:" $ker
echo -e "\nMEMORY STATUS:"
echo -e "=====
echo -e "Total Memory:" $tot 'MB'
echo -e "Memory In Use:" $use 'MB'
echo -e "Free Memory:" $fre 'MB'
echo -e "Cached Memory:" $cac 'MB'
echo -e "\n=> Hostname:" $ho
echo -e "\n=> Currnt users:" $curc
echo -e "\n=> Server's $lo
echo -e "\n=> Your IP Address Is:" $isp '\n'
pause
```

Save the file and exit your text editor. Next, let's change the permission of the script file, as follows:

```
# chmod 755 server_info.sh
```

Run the following script to get the information:

```
## ./server_info.sh
```

– Ranjithkumar T., ranjith.stc@gmail.com



Viewing configuration files without comments and blank lines

Comments and blank lines can be great. They provide context and can make configuration files easier to read. However, if you need to see only the current active configuration lines without comments and blank lines, either of the following commands will do exactly that.

```
grep -Ev '^#|^$' /etc/login.defs
```

Or:

```
egrep -v '^#|^$' /etc/login.defs
```

– Krishna Murthy, gtk321@rediffmail.com



Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in OSFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.opensourceforu.com. The sender of each published tip will get a T-shirt.