



Figure 5: Mercury Tours website




Figure 6: Selecting Assert

Table 1: The three categories of Selenium commands

Actions	These are commands that directly interact with page elements. Example: The 'click' command is an action because you directly interact with the element you are clicking on. The 'type' command is also an action because you are putting values into a text box, and the text box shows them to you in return. There is a two-way interaction between you and the text box.
Accessors	These are commands that allow you to store values to a variable. Example: The 'storeTitle' command is an accessor, because it only 'reads' the page title and saves it in a variable. It does not interact with any element on the page.
Assertions	These are commands that verify if a certain condition is met. There are three types of assertions. • Assert: When an 'assert' command fails, the test is stopped immediately. • Verify: When a 'verify' command fails, Selenium IDE logs this failure and continues with the test execution. • WaitFor: Before proceeding to the next command, 'waitFor' commands will first wait for a certain condition to become true. ◦ If the condition becomes true within the waiting period, the step passes. ◦ If the condition does not become true, the step fails. Failure is logged, and test execution proceeds to the next command. ◦ By default, the timeout value is set to 30 seconds. You can change this in the Selenium IDE <i>Options</i> dialogue box under the <i>General</i> tab.



Figure 7: User name and password




Figure 8: Selenium editor




Figure 9: Generated script




Figure 10: Save script as

runs successfully.

3. In case there is any discrepancy from the test condition you've added, then that particular step will be highlighted in red.

11. You can see the same steps also reflected in the Selenium editor.
12. Now you need to toggle off the *Record* button. Your Selenium editor will show an auto generated script as seen in Figure 9.

13. In the *File* menu, select 'Save Test Case'. Alternatively, you can simply press *Ctrl+S*. It will save whatever script we have generated as a standalone test case, which we can execute any number of times.

Running the script

To run the script, follow these steps:

1. Go to the Selenium IDE and click on the playback button.
2. This will execute each step in the script flawlessly, and you will see it turn green if it