

You can change the latest version. The current latest version is 3.2.

- iii) Now, Apache Cassandra will be available for installation through Yum.

```
$ sudo yum install datastax-ddc
```

The above command will also install the Cassandra utilities such as *sstablelevelreset*, *sstablemetadata*, *sstableofflinerelevel*, *sstablepairedset*, *sstablesplit* and *token-generator*.

- iv) Cassandra is now installed as a service. To check its status, use the following command:

```
$ sudo service cassandra status
```

Start Cassandra as follows:

```
$ sudo service cassandra start
```

To stop Cassandra, use the following command:

```
$ sudo service cassandra stop
```

Start the Cassandra command line, as follows:

```
$ cqlsh
```

Installing Apache Cassandra 3.x on the latest Ubuntu LTS or Debian stable release

The prerequisites are:

- a. Advanced package tool should be installed
- b. Root or non-root user with sudo privileges
- c. Oracle Java Platform, Standard Edition 8 (JDK) or OpenJDK 8. JDK is recommended for Cassandra installation, as it has some tools that are not in JRE.
- d. Python 2.7

Installation steps

Check the Java version as follows:

```
$ java -version
```

- i. If Oracle Java is used, the results should look like what's shown below:

```
openjdk version "1.8.0_72-internal"
```

```
OpenJDK Runtime Environment (build 1.8.0_72-internal-b05)
```

```
OpenJDK 64-Bit Server VM (build 25.72-b05, mixed mode)
```

- ii. Create a new source list *cassandra.sources.list* under */etc/apt/sources.list.d/*:

```
$ echo "deb http://debian.datastax.com/datastax-ddc 3.2 main"
| sudo tee -a /etc/apt/sources.list.d/cassandra.sources.list
```

- iii. Allow installation of the Oracle JVM instead of the OpenJDK JVM.

Open the */etc/apt/sources.list* file, and find the line that describes your source repository for Debian. Add 'contrib non-free' at the end of the line and save the file. For example:

```
deb http://some.debian.mirror/debian/ $distro main contrib
non-free
```

- iv. Add the DataStax repository key to your aptitude trusted keys, as follows:

```
$ curl -L https://debian.datastax.com/debian/repo_key | sudo
apt-key add -
```

- v. Update the *apt-get* repository and install Apache Cassandra, as follows:

```
$ sudo apt-get update
```

```
$ sudo apt-get install datastax-ddc
```

- vi. To verify the installation, check the status, as shown below:

```
$ sudo service cassandra status
```

Start Cassandra, as follows:

```
$ sudo service cassandra start
```

Stop Cassandra, as shown below:

```
$ sudo service cassandra stop
```

Setting up Cassandra on Windows

The prerequisites are:

- a. Java 8
- b. 32-bit systems require the Visual C++ 2008 runtime

Installation steps

Download the Windows installer from <http://www.planetcassandra.org/cassandra/>.

- i. Download the link <http://downloads.datastax.com/datastax-ddc/datastax-ddc-64bit-3.2.1.msi>.

After a successful download, run the installer and follow the set-up wizard to install. While installing, accept the option 'Automatically start Data Stax DDC Service' to automatically start the services whenever the computer reboots.

When your installation is done successfully, you will be able to see the new program, 'DataStax Distribution of Apache Cassandra' under *Start Menu-> All Programs*.