

```

public class readFromFile {
    public static void main(String[] args) throws IOException{
        if(args.length==1)
        {
            Configuration conf = HBaseConfiguration.create(new
            Configuration());
            HBaseAdmin hba = new HBaseAdmin(conf);
            if(!hba.tableExists(args[0])){
                HTableDescriptor ht = new HTableDescriptor(args[0]);
                ht.addFamily(new HColumnDescriptor("sample"));
                ht.addFamily(new HColumnDescriptor("region"));
                ht.addFamily(new HColumnDescriptor("time"));
                ht.addFamily(new HColumnDescriptor("product"));
                ht.addFamily(new HColumnDescriptor("sale"));
                ht.addFamily(new HColumnDescriptor("profit"));
                hba.createTable(ht);

                System.out.println("New Table Created");
                HTable table = new HTable(conf,args[0]);
                File f = new File("/home/training/Desktop/data");
                BufferedReader br = new BufferedReader(new FileReader(f));
                String line = br.readLine();int i=1;String rowname="row";
                while(line!=null && line.length()!=0){
                    System.out.println("Ok till here");
                    StringTokenizer tokens = new StringTokenizer(line, ",");
                    rowname = "row"+i;
                    Put p = new Put(Bytes.toBytes(rowname));
                    p.add(Bytes.toBytes("sample"),Bytes.
                    toBytes("sampleNo."),Bytes.toBytes(Integer.parseInt(tokens.
                    nextToken())));
                    p.add(Bytes.toBytes("region"),Bytes.toBytes("country"),Bytes.
                    toBytes(tokens.nextToken()));
                    p.add(Bytes.toBytes("region"),Bytes.toBytes("state"),Bytes.
                    toBytes(tokens.nextToken()));
                    p.add(Bytes.toBytes("region"),Bytes.toBytes("city"),Bytes.
                    toBytes(tokens.nextToken()));
                    p.add(Bytes.toBytes("time"),Bytes.toBytes("year"),Bytes.
                    toBytes(Integer.parseInt(tokens.nextToken())));
                    p.add(Bytes.toBytes("time"),Bytes.toBytes("month"),Bytes.
                    toBytes(tokens.nextToken()));
                    p.add(Bytes.toBytes("product"),Bytes.
                    toBytes("productNo."),Bytes.toBytes(tokens.nextToken()));
                    p.add(Bytes.toBytes("sale"),Bytes.toBytes("quantity"),Bytes.
                    toBytes(Integer.parseInt(tokens.nextToken())));
                    p.add(Bytes.toBytes("profit"),Bytes.toBytes("earnings"),Bytes.
                    toBytes(tokens.nextToken()));
                    i++;
                    table.put(p);
                    line = br.readLine();
                }
                br.close();
                table.close();
            }
            else
                System.out.println("Table Already exists.Please enter another

```




Figure 5: The Eclipse program



Figure 6: Output after inserting record in HBase

```

table name";
}
else
    System.out.println("Please Enter the table name through
    command line");
}
}

```

Before running the above Java code make sure that you have the following JAR files in the build path, as the program is dependent on these files, namely, *commons-logging-1.0.4*; *commons-logging-api-1.0.4*; *hadoop-core-0.20.2-cdh3u2*; *hbase-0.90.4-cdh3u2*; *log4j-1.2.15* and *zookeeper-3.3.3-cdh3u0*.

Run the program after providing the table name through the command line, as shown in Figure 5.

The output of scanning the table is shown in Figure 6.

To conclude, HBase is quite useful for real-time read write operations on big data sets which need to be stored on HDFS. 

By: Ashish Kumar Sinha

The author is a software engineer based in Bengaluru. A software enthusiast by heart, he is passionate about using open source technology and sharing it with the world. He can be reached at ashi.sinha.87@gmail.com