

- 3) Now, in the second terminal, perform the 'cat' operation on the named pipe as follows:

```
[bash]$ cat telecooperation.fifo
```

- 4) Switch back to the first terminal and execute the following few commands:

```
[bash]$ date  
[bash]$ hostname  
[bash]$ uname
```

Now, on the second terminal, you can observe the first terminal's real-time broadcasting.

– Narendra Kangralkar,
narendrakangralkar@gmail.com



Make a bootable USB from an ISO

If you're tired of burning ISO images to DVDs, you can make bootable USB disks to install the *nix OS with ease, as follows:

```
# dd if=/path/to/iso of=/dev/<usb_device>
```

For example...

```
## dd if=/home/raghav/Fedora_xx.iso of=/dev/sdb
```

...where *sdb* is the name of the USB device attached.
Boot from the USB stick and install the OS.



Note: The 'dd' command should be used with extra care as wrong usage can lead to data loss.

– Raghavendra Bijjula, raghavabijjula@gmail.com



Resetting a forgotten root password

This method of resetting a forgotten root password works on most Linux distributions. I have tested this method already in Ubuntu, Linux Mint, RHEL, CentOS and Kali Linux.

Boot the system and from the boot menu, select the kernel for which you have to change the administrative password with the help of the navigation key. In my case it is:

```
Linux Mint 15 Cinnamon 64-bit, 3.8.0-19-generic (/dev/  
sda9)
```

Now edit that kernel by pressing the key 'e'.

Then you have to edit the line which starts with 'Linux /boot/'.

You have to make two changes:

1. Edit 'ro' into 'rw'.

2. And at the end of the line, add the following command:

```
init = /bin/bash
```

Now boot using the edited configuration by pressing the 'F10' key.

This will direct you to a command prompt:

```
(none)/#  
Change the password  
(none)/# passwd  
Enter new unix Password:  
Retype new unix Password:  
passwd: password updated successfully
```

Now, you have to synchronise (optional):

```
(none)/#sync
```

Reboot the system to make the changes effective.

– Sumesh Nair, sumesh1389@gmail.com



Send desktop notifications using a shell program

The *notify-send* command is used to send desktop notifications, which can be used to inform the user about an event or display some form of information without getting in the user's way.

The syntax is:

```
# notify-send <message>
```

The above line can be added in the shell program after completing a specific event, with the particular message that informs the user of that event.

```
# notify-send "Hello programmer..."
```

This displays the message "Hello programmer..." just below the top right corner of the monitor or near the notification area of the desktop.

– Nagaraju Dhulipalla, nagarajunice@gmail.com



Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems – take them head on, defeat them! We invite you to share your tips and tricks with us for publication in *OSFY* so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.opensourceforu.com. The sender of each published tip will get a T-shirt.