

Table 2: Drivers supported by Selenium WebDriver

Browser	Driver	Command	Description
Chrome	Chrome Driver	WebDriver driver = new ChromeDriver();	ChromeDriver is part of the Project Chromium. To work with ChromeDriver both the Chrome browser and ChromeDriver executable files should be present on your system. ChromeDriver can be downloaded from https://sites.google.com/a/chromium.org/chromedriver/home .
Internet Explorer	Internet Explorer Driver	WebDriver driver = new InternetExplorerDriver();	It is a standalone server. It is available in 32-bit and 64-bit versions. It can be downloaded from http://docs.seleniumhq.org/download/ .
Firefox	Firefox Driver	WebDriver driver = new FirefoxDriver();	WebDriver can drive Firefox without the need of a driver server. It uses the Firefox plug-in to control the Firefox browser. It is faster than the Internet Explorer Driver.
HtmlUnit	HtmlUnit driver	WebDriver driver = new HtmlUnitDriver();	It is based on HtmlUnit, which is a Java based implementation. It is platform independent. It is the fastest implementation of WebDriver.




Figure 3: Properties window

- Add all the files from the *libs* folder as well as the *jar* files, and click on the OK button.
- After following these steps, all the Selenium files will be imported in the Java project and you can start working with Selenium WebDriver to create a script.

Selenium WebDriver commands for locating UI elements

Locating the elements of the Web page is one of the very important tasks in automation testing when using Selenium WebDriver. These elements are used to navigate to the Web page automatically. There are various ways to locate the elements, as shown in Table 1.

Selenium WebDriver

Selenium WebDriver supports various types of drivers through which Web applications can be accessed (Table 2). It overcomes




Figure 4: Lib files




Figure 5: Web drivers



Figure 6: Inspecting the element