

- Set the URL to *error.jsp*.

Forward the request to the URL.

To create the JSP files, right click on *Project LoginDemo*, select *New*, click on *JSP*, type the file name and in *Folder* add *WEB-INF/jsp*.

In *welcome.jsp*, we will display user data that is shared by our servlet. Code for *welcome.jsp* is shown below. We will use *{object.fieldname}* to display the data.

```
<%@page import="edu.ashish.beans.UserBean"%>
<%@page contentType="text/html" pageEncoding="UTF-8"%>
<!DOCTYPE html>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
<title>Welcome Page</title>
</head>
<body>
<h1>Welcome ${userdata.firstname}</h1>
<table>
<tr> <td>Email <td> ${userdata.email} </tr>
<tr><td>First Name <td> ${userdata.firstname}</tr>
<tr><td>Last Name <td> ${userdata.lastname} </tr>
</table>
</body>
</html>
```

In the same way, create *error.jsp*, which is used to display errors in red colour as shown below.

```
<%@page contentType="text/html" pageEncoding="UTF-8"%>
<!DOCTYPE html>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
<title>Error Page</title>
</head>
<body>
<h1>We are sorry something is wrong.</h1>
<h3><font color="red">${error}</font></h3>
</body>
</html>
```

Edit *index.html*, and in the *form* tag, add action attribute with value as *controller*. Create two text boxes for user input as shown in the below code.

```
<!DOCTYPE html>
<html>
<head>
```

```
<title>Main Page</title>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
</head>
<body>
<div><center><h2>Welcome to Login and Register Page/<h2></center></div>
<table>
<tr><td><h4>Sign in </h4>
<form action="controller">
<table>
<tr>
<td>Email id</td>
<td><input type="text" name="email"/>
</tr>
<tr>
<td>Password</td>
<td><input type="password" name="pwd"/>
</tr>
<tr>
<td><td>
<td><input type="submit" value="Log in"/>
</tr>
</table>
</form>
</table>
</body>
</html>
```




Figure 11: Application structure

We can see *Projects* and its file, which will look like what's shown in Figure 11.

When we run the application, we can see *index.html*.

Fill the data, click on the *Login* button, and it will display *welcome.jsp* if it is correct.

In case of error, it will display *error.jsp*.

We have almost created an MVC application. The article is just for understanding the MVC approach and may need a few changes while being put into practice, such as removing the database code from the Servlet/controller. **END** 

By: Ashish Singh Bhatia

The author is a technology enthusiast and a FOSS fan. He loves to explore new technology, and to work on Python and Java languages. He can be reached at ast.bhatia@gmail.com and he blogs at <https://openfreeidea.wordpress.com/>.