

Tuesday	1.50	Done
Wednesday		
Thursday		
Friday		
Saturday		
Sunday		

You can also use a spreadsheet formula on these tables to perform calculations. For example:

```
* TODO College...
* DONE Home [2/2]...
* Recreation [50%]
  - [X] Read newspaper
  - [ ] Meditate

| Day | Time | Status |
|-----+-----+-----|
| Monday | 1.25 | Done |
| Tuesday | 1.50 | Done |
| Wednesday | | |
| Thursday | | |
| Friday | | |
| Saturday | | |
| Sunday | | |
|-----+-----+-----|
| Total | 2.75 | |
#*TBLFM: @9$2=vsum(@2$2..@8$2)
```

Exporting

The Org file can be exported to multiple output formats (TeX, HTML, ASCII, PDF, etc). Using C-c C-e will produce a buffer with the 'Org Export Dispatcher' menu to select an exporter. This is shown in Figure 1.

You can also write your own backend customisations to suit your needs.

Literate programming

Donald Knuth coined the term 'literate programming' in




Figure 1: Org Export Dispatcher

1984. To quote him:

"I believe that the time is ripe for significantly better documentation of programs, and that we can best achieve this by considering programs to be works of literature. Hence, my title 'Literate Programming'.

"Let us change our traditional attitude to the construction of programs. Instead of imagining that our main task is to instruct a computer what to do, let us concentrate rather on explaining to human beings what we want a computer to do."

Org-mode supports this style of programming using Babel. You need to activate the support for the programming languages in your GNU Emacs startup file. For example, the following code snippet helps to execute Bash shell scripts.

```
(org-babel-do-load-languages
 'org-babel-load-languages
 '((sh . t)
 ))
```

Consider a shell command to find the disk usage. You can create an Org file, and enclose the command in a Babel code block as shown below:

```
#+BEGIN_SRC sh
df -h
#+END_SRC
```

When you press C-c C-c on this code block, you will be prompted with the string, "Evaluate this sh code block on your system? (yes/no)." if you input 'yes', the output is produced in the Results section as shown below:

```
#+RESULTS:
| Filesystem | Size | Used | Avail | Use% | Mounted on |
|-----+-----+-----+-----+-----+-----|
| udev       | 1.9G | 0     | .9G   | 0%   | /dev       |
| tmpfs      | 384M | 6.0M | 378M  | 2%   | /run       |
| /dev/sda1  | 913G | 75G   | 792G  | 9%   | /          |
| tmpfs      | 1.9G | 57M   | 1.9G  | 3%   | /dev/shm   |
| tmpfs      | 5.0M | 4.0K  | 5.0M  | 1%   | /run/lock  |
| tmpfs      | 1.9G | 0     | 19G   | 0%   | /sys/fs/cgroup |
| tmpfs      | 384M | 64K   | 384M  | 1%   | /run/user/1000 |
```

You can learn more about Babel from its web page <http://orgmode.org/worg/org-contrib/babel/>.

A mobile version of Org-mode is also available as free and open source software. You can use a third party service to sync your Org files between your mobile and system. Since the files are plain text, they can also be revision controlled using Git or any version control software.

Please refer to the Org reference manual at <http://orgmode.org/docs> for more tips, customisation options and documentation. 

By: Shakthi Kannan

The author is a Free Software enthusiast who blogs at shakthimaan.com.