

instance called `get_iframe`. The argument in this method is the name or ID or index:

```
with browser.get_iframe('testframe') as iframe:
    iframe.do_stuff()
```

For handling alerts and prompts, the following fragments of code C can be employed:

```
# For alerts
alert = browser.get_alert()
alert.text
alert.accept()
alert.dismiss()
```

```
# For prompts
```

```
prompt = browser.get_alert()
prompt.text
prompt.fill_with('this is a sample text')
prompt.accept()
prompt.dismiss()
```

Handling HTTP exceptions

Splinter allows you to handle the exceptions that might arise

while trying to perform operations:

```
try:
    browser.visit('http://opensourceforu.com/')
except HttpErrorResponse, e:
    print "The Operation Failed with status code %s and reason %s" % (e.status_code, e.reason)
```

The complete API documentation for Splinter is available at <https://splinter.readthedocs.org/en/latest/api/index.html>.

To summarise, Splinter makes the automation of Web application acceptance testing simple. 

References

- [1] <https://splinter.readthedocs.org/en/0.7.3/index.html>
- [2] <https://wiki.python.org/moin/PythonTestingToolsTaxonomy>

By: Dr K.S. Kuppusamy

The author is assistant professor of computer science at Pondicherry Central University. He has more than 10 years of teaching and research experience in academia and in industry. His research interests include accessible computing, Web information retrieval and mobile computing. He can be reached via mail at kskuppu@gmail.com.

India's #1 Website For Electronics Engineers Working Across The Globe

Established: 1998 | Registered Users: 300,000+

Monthly Statistics

Page Impressions: 750,000+

Unique Techies: 150,000

electronicsforu.com

If it's electronics, it's here



For any queries, please contact our team at efyengq@efy.in OR +91-11-26810601