



TIPS & TRICKS

How to check the number of processes and threads

Systems administrators or developers often need to check the number of processes, or the threads running per process, on a Linux based server or computer. This can be easily done using the `ps` and `grep` commands, as given below.

Enter the following command:

```
$ps -ef | grep java
```

This gives the number of Java processes running. Next, use the following command:

```
$ps -eLf | grep -c java
```

This gives you the number of threads used by the Java programs.

—Sumeet Patil, sumeetp1991@gmail.com

How to make the Mint file manager bookmarks show up

If your Linux Mint file manager bookmarks won't show up in your file when you open and save dialogue boxes (and this happens because they use two different storage files for bookmarks), the following terminal command will solve the problem:

```
mv ~/.config/gtk-3.0/bookmarks ~/.config/gtk-3.0/bookmarks~;
ln -s ~/.gtk-bookmarks ~/.config/gtk-3.0/bookmarks
```

If for any reason you wish to revert to the earlier state, just issue the following command:

```
rm ~/.config/gtk-3.0/bookmarks; cp ~/.config/gtk-3.0/
bookmarks~ ~/.config/gtk-3.0/bookmarks
```

—Ansuman Datta, webmaster@auucklandandwhich.org

Edit and navigate easily using Vim

Vim has an inbuilt `netrw` listing, which you can use to edit and navigate through files easily. To do so, just go to

the folder and type the following command:

```
$ vim .
```

Or use the one below:

```
$ vim <folder path>
```

Now, there will be a listing of all the files and directories in the folder. You can navigate through them using your keyboard. Clicking `Enter` on a file can open the file for editing. After editing it, press `':w'` for saving, `':E'` or `':Ex'` for going back to the listing or `':q'` to exit.

To create a new file in the present folder, press `''`.

To rename a file, press `'R'`.

To remove a file, press `'D'`.

—Sajin M. Prasad, sajinprasadkm@gmail.com

How to search for and replace a string in the file name

As a developer, you may sometimes want to rename a file in a directory by substituting a certain string in the file name. The following one line tip in the Linux shell will help you to achieve this.

```
for file in `ls "oldname"`; do mv $file $(echo $file | sed -e
"s/oldname/newname/g"); done
```

Here, `'oldname'` is the search string and `'newname'` is the replacement string.

The `for` loop will iterate and file the `'file'` variable with every instance of the files found. The `'sed'` command will replace the found string with a replacement string, and pass it as the second parameter for the `'mv'` command.

Here is an example of how to rename all files that have the string `'oldname'` in their file names, which need to be replaced with `'newname'`.

```
[yogindar@yogindar-server1 test]$ touch oldname.txt
oldname.c oldname-test.c test-oldname.c
```