



Figure 1: ownCloud

folder as shown below:

```
$ sudo sh -c "echo 'deb http://download.owncloud.org/
download/repositories/9.1/Ubuntu_16.04/' >> /etc/apt/
sources.list.d/owncloud.list"
```

Use the `apt-get update` command to make `apt` aware of the change, as follows:

```
$ sudo apt-get update
```

Install the LAMP (Linux, Apache, MySQL and PHP) server:

```
$ sudo apt-get install lamp-server^
```

You will be prompted with a window to create a password for the MySQL root user. Enter a secure password, and use the tab key and the space bar to select the OK button.

Add a MySQL database

The next step is to create a MySQL database for ownCloud. Log in to MySQL by using the following command:

```
mysql --defaults-file=/etc/mysql/debian.cnf
```

This opens up the MySQL command line prompt. Enter the following SQL commands to create a user with the name 'owncloud' and a database of the same name. Replace the word 'mysecurepassword' with your own password in the commands, as shown below:

```
-> CREATE DATABASE owncloud;
-> CREATE USER owncloud@localhost IDENTIFIED BY
'mysecurepassword';
-> GRANT ALL PRIVILEGES ON owncloud.* TO owncloud@localhost;
-> flush privileges;
-> quit
```

Install ownCloud using the `apt-get install` command. The 'owncloud' package will install all the required dependencies.




Figure 2: MySQL root password

```
$ sudo apt-get install owncloud
```

Restart the Apache server to update the changes made to Apache's `config` directory.

```
$ sudo service apache2 restart
```

A quick start and set-up of the admin account

Open the Web interface of ownCloud by navigating to `https://localhost/owncloud/`.

If ownCloud is hosted in a server, you can get to the Web interface using the server domain or the IP address of the server (`https://server_domain_or_IP/owncloud`).

If a self-signed certificate is being used, you are likely to be presented with a warning because the certificate is not signed by one of your browser's trusted authorities. This is expected and normal. We are only interested in the encryption aspect of the certificate, not the third-party validation of our host's authenticity. Click the appropriate button or link to proceed to the ownCloud admin page.

You should see something like what is shown in Figure 4.

When the page loads, you will be prompted with a form to enter a user name (for security reasons, it is recommended that you do not use `admin` as the user name) and password to create an admin account.

The default database used by ownCloud is SQLite, which should not be used in production. To change it to MySQL, click on the `Storage & database` link. Leave the `Data` folder settings as they are and click on the MySQL/MariaDB tab to use MySQL. Enter the database information that you




Figure 3: Creating a database named 'owncloud' using SQL