

UI5 development tools are available at <https://tools.hana.ondemand.com/luna> as shown in Figure 2.

Select the added repository, check the UI development kit for HTML5 and install the same.

Getting started

You can download the OpenUI5 library from <http://openui5.org/download.html>. There, you can find both the runtime library and the SDK. The runtime package contains everything needed to run a UI5 application, including all mobile resources. Deploy the SDK on your own server to access the documentation offline, or you can find it at <https://sapui5.netweaver.ondemand.com>.

CDN (Content Delivery Network)

You can use OpenUI5 without downloading resources. The network of distributed servers provides OpenUI5 resources from the closest location to the user. Use the link <https://openui5.hana.ondemand.com/1.36.5/resources/sap-ui-core.js> for a specific OpenUI5 version.

Use the link <https://openui5.hana.ondemand.com/resources/sap-ui-core.js> for the latest stable OpenUI5 resources.

Let's start with 'Hello World'

The following example prints the 'Hello World' message using CDN.

```
<!DOCTYPE html>
<html>
<head>
<meta http-equiv='X-UA-Compatible' content='IE=edge' />
<title>Hello World</title>

<script id='sap-ui-bootstrap'
  src='https://openui5.hana.ondemand.com/1.36.5/resources/
  sap-ui-core.js'
  data-sap-ui-theme='sap_bluecrystal'
  data-sap-ui-libs='sap.m'
  data-sap-ui-compatVersion='edge'
  data-sap-ui-preload='async'>
</script>

<script>
  sap.ui.getCore().attachInit(function () {
    new sap.m.Text({
      text: "Hello World"
    }).placeAt("content");
  });
</script>

</head>
<body class='sapUiBody'>
  <div id='content'></div>
```




Figure 2: Add repository




Figure 3: Install tool kit

```
</body>
</html>
```

Description

In this code snippet, the first script tag is responsible for fetching OpenUI5 resources and it sets some initial parameters like:

- **data-sap-ui-theme** - OpenUI5 supports theming; this property is used to set the required theme.
- **data-sap-ui-libs** - This property loads the libraries mentioned with the namespace.

If you want to develop the program offline, then you can deploy the downloaded resources in your own server and use the deployed resource path to load the resources in the HTML file's `src` property of the script tag.

The second script tag represents the actual OpenUI5 code. In this case, the simple `sap.m.Text` control is rendered. `placeAt('content')` indicates that the control is placed inside the `div` tag, which is the only `div` in the body element in the above HTML code.

By: Rahul Inamadar

The author is a software developer and is passionate about JavaScript. He likes to explore new technologies. He has worked on SAPUI5/OpenUI5 (JavaScript framework), SAP HANA Cloud Platform, Java/J2EE and JavaScript. He can be contacted at 23rahul91@gmail.com.