



Figure 1: Sample example running in the browser

installed; so let us test it by creating a sample 'Hello World' example.

In our project directory, create a file named *website.js* and add the following code:

```
var express = require('express');
var app = express();
app.get('/', function (req, res) {
  res.send('<h1>Open Source For You!</h1>');
});
app.listen(3000, function () {
  console.log('Example app listening on port 3000!');
});
```

The above code starts a server and listens on port 3000 for connections. It also responds with the text 'Open Source For You!' in the header 1 HTML formatting for requests made to the root URL (/), and for every other path, it will respond with a message '404 Not Found'.

To execute, run the following command in the *project* folder:

```
C:\project>node website.js
```

Then, load *http://localhost:3000/* in the browser to see the output.

If you see the text printed in the browser, as shown in Figure 1, then you are all set for creating a website using Bootstrap and Express.js.

Creating a website

We are going to use Bootstrap and basic HTML for the view, and the Express.js framework as a Web server and to handle routes.

You can download all the necessary Bootstrap files from *http://getbootstrap.com/* or you can use files from CDN (Content Delivery Network).

For our sample website, we are going to use Bootstrap files from CDN.

Let's start by creating views first; our website will have three Web pages.

1. *index.html*: Index page of our sample website.
2. *product.html*: The product page of our sample website, where we will add some sample information about products.
3. *about.html*: The 'About us' page of our sample website, where we will add contact details, etc.

Creating the HTML pages

Navigate to our *project* folder, and create a new folder called 'views' in it. After that, open Notepad or any of your favourite code editors, and copy the following HTML code:

```
<!doctype html>
<html lang="en">

<head>
<meta charset="UTF-8">
<title>Sample website using Bootstrap and ExpressJS</title>

<!--CDN Links-->
<script src="//ajax.googleapis.com/ajax/libs/jquery/1.11.1/jquery.min.js"></script>
<link rel="stylesheet" href="http://maxcdn.bootstrapcdn.com/bootstrap/3.3.1/css/bootstrap.min.css">
<script src="//maxcdn.bootstrapcdn.com/bootstrap/3.3.1/js/bootstrap.min.js"></script>

<script src="website.js"></script>
</head>
<body>
<div>
<div>
<nav class="navbar navbar-inverse" role="navigation"
style="padding-left:130px;">
  <ul class="nav navbar-nav">
    <li class="active"><a href="/">Home<span class="sr-only">(current)</span></a></li>
    <li><a href="/product">Products</a></li>
    <li><a href="/about">About us</a></li>
  </ul>
</nav>
</div>
<br/>
<div class="jumbotron"> <p>
This is place to put your Sample Content.
</p></div>
</div>
</body>
</html>
```

Save the above code as *index.html* in the *views* folder, which is present inside the folder named *project* (i.e., at C:\project\views>).

As you can see in the above code, we have used Bootstrap and jQuery files from CDN. Also, we have included the *website.js* file, where we are going to write routing logic for this sample website. In the above code, we have also used Bootstrap's Navbar class to provide navigation to the HTML pages present in the *views* folder. Since this is the index page, we have set the class of the *Home* link in the navbar as 'active'.