

Figure 2: Server running and listening for connections on a port

```
app.use('*',function(req, res){
  res.send('Error 404: Not Found!');
});

app.listen(3000,function(){
  console.log("Server running at Port 3000");
});
```

Here is an explanation of the code snippet given above.

First, we load the dependencies, i.e., the Express.js framework. We are also loading the `router()`, which is the built-in routing service provided by the Express.js framework.

Since we have stored our HTML files in the 'views' folder, we have assigned the path using the `__dirname` keyword, which basically points to our current working directory.

Then, we used `app.use('/', router)` since we are using routes in the code.

After this, we define the routes: `/product` and `/about`. These route definitions have a `sendFile()` function, which is a built-in function and is designed to send files to the Web browser. For example, in our case, in the `index.html` page, if the user clicks on any one of the Navbar links, then the `router.get()` function provides the file associated with that particular link.

And if the user enters some invalid routes, we can also display the custom error message by using the `* regex` pattern in the `app.use()` function.

Finally, we declare the port number that listens to connections using the `app.listen()` function.

Your *project* folder must end up with the following directory structure:

```
-- node_modules
-- views
+ -- index.html
+ -- product.html
```




Figure 3: The website we created, running in the browser

```
+ -- about.html
package.json
website.js
```

The above *project* directory structure has two folders (named `node_modules` and `views`) and two files (named `package.json` and `website.js`). The `views` folder contains three HTML files named `index.html`, `product.html` and `about.html`.

Running the website

To execute, run the following command in the project folder:

```
C:\project>node website.js
```

The message shown in Figure 2 will be displayed.

Then, load the address `http://localhost:3000/` in the browser to see the output.

You should be able to see your first website created using Bootstrap and the Express.js framework, as shown in Figure 3. **END**

References

- [1] <http://getbootstrap.com/>
- [2] <https://expressjs.com/>
- [3] <https://en.wikipedia.org/wiki/Express.js>
- [4] <http://www.w3schools.com/bootstrap/default.asp>

By: Aniket Eknath Kudale

The author is an open source enthusiast who has more than two years of experience as a software engineer at Tibco Software Inc., Pune. You can reach him at kudale@aniket.co

**Know the Leading Players
in Every Sector of the
Electronics Industry**

www.electronicseb2b.com

**ACCESS ELECTRONICS
B2B INDUSTRY WITH A**

CLICK OF A BUTTON

Log on to www.electronicseb2b.com and be in touch with the Electronics B2B Fraternity 24x7