

Finally, install the Buku package with the command shown below:

```
$sudo apt-get install buku
```

The basics

Each bookmark in Buku contains the following four parts:

- URL
- Title
- Tags
- Comments

URL: This holds the address of the particular Web page that you want to bookmark. Do note that all the URLs are unique in Buku, and if your URL contains special characters such as ';', ',', '&' and '()' please enclose such URLs with single or double quotes, so that special characters in the URL don't get interpreted by the shell.

Title: A title is optional in Buku because as soon as you have added a bookmark in Buku, it will automatically fetch the title from the URL through the Web and insert it into the corresponding bookmark. But if you want to set the title by yourself, you can use the `-title` option to do so.

By default, all the titles are changeable ($N=0$), but if you want to make a title constant, you can set the title immutable value ($N=1$).

Tags: These are essential in Buku because, through their effective use, bookmarks can be identified, searched and linked with other relevant bookmarks. Buku uses the comma to separate tags, so you cannot place a comma within a tag.

Comments: Comments are additional information you give to the bookmarks for your own convenience. These can be changed anytime you wish. Comments can be brief and unique so that each bookmark can be recognised easily.

Buku stores all the bookmarks in a single database file. Each URL is unique in the database. Besides, bookmarks are accessed through their index in the database. So whenever we want to add, delete or update bookmarks, we need to provide the index of the bookmark in the database.

Adding a bookmark

To add a bookmark, you need to use the `(-a)` option along with the Buku command, followed by the URL, tags and comments.

For example, the following command will add a bookmark on the Wikipedia page for 'Free Software':

```
$buku -a https://en.wikipedia.org/wiki/Free_software
wiki,free_software,wikipedia -c Wikipedia article on Free
Software
```

In the above example, we can see the URL of the Wikipedia page that we want to bookmark. After that, we have tags as 'wiki', 'free_software' and 'wikipedia' separated by the comma and finally, the `-c` option will show the

comment for the bookmark.

Figure 1 illustrates the output in the terminal after the bookmark has been successfully added to the Buku database.

If you're uncomfortable with this structure, you can add your bookmarks using the editor with the `-w` option, as shown below:

```
$buku -w 'nano-w'
```

The above command will open the nano editor along with the skeleton structure for adding a bookmark. All you need to do is fill in the blanks in the editor and save it.

Updating a bookmark

We can update a bookmark by using the `(-u)` option. Buku is so flexible that even individual elements of the bookmark can be updated separately while the others remain intact.

For each update, you need to provide the index of that bookmark. If you're not sure of the index number of the bookmarks, you can view all the bookmarks along with their index numbers by using the following command:

```
$buku -p
```

For instance, if a website has changed its name, we can



Figure 1: Bookmark added output




Figure 2: Bookmark editor




Figure 3: Bookmark view all