

the file is encrypted. When you try to view the bookmarks, you will get an error message that the database needs to be unlocked first.

To decrypt the database file, you need to issue the command with the option `-k` so that you can access the bookmark database, as shown below:

```
$buku -k
```

After you have provided the right password, you will see the database is decrypted.

Please note that after decryption, the bookmark database will remain in the unencrypted state, so please lock the database when not in use.

Importing and exporting

Buku supports HTML, Markdown and DB formats for importing and exporting bookmarks. And you can export all the bookmarks to one of the supported formats by using the `-e` option.

```
$buku -e bookmarks.html
```

The above command will export the bookmarks in the HTML format.

If you want to export only specific bookmarks from Buku, you can use tags. That way, only the bookmarks that have those particular tags get exported.

For example, if you want to export the bookmarks that have the tags `'privacy'`, you may modify the above command as follows:

```
$buku -e bookmarks.html --tag privacy
```

For importing bookmarks, you can either use the automatic import option to import all the bookmarks from your browser, or you can import the bookmarks from one of the supported formats mentioned in the above sections.

To use the automatic import, use `--ai` along with the Buku command, as shown below:

```
$buku --ai
```

You will be asked if the parent folder from the browser can be used for tags; choose the `'Yes'` or `'No'` option, as you wish.

The next question will be: Which browser can be used to import bookmarks? For example, I have Google Chrome and Firefox on my system. I wish to import bookmarks from Chrome, so I will give the response `'y'` to Chrome, after which it will import the bookmarks from Google Chrome and add them to the Buku database.

To manually import the bookmarks from HTML or any of the supported formats, use the following command:

```
admin@JaxSparrow ~ $ buku -l
Password:
Password:
File encrypted
admin@JaxSparrow ~ $
```

Figure 6: File encrypted

```
admin@JaxSparrow ~ $ buku -k
Password:
File decrypted
_
```

Figure 7: File decrypted

```
admin@JaxSparrow ~ $ buku --shorten 'https://en.wikipedia.org/wiki/Battle_of_Warsaw_(1920)'
http://tiny.im/x00on _
```

Figure 8: Shortend URL

```
$buku -i bookmarks_frm_chrome.html
```

Based on your responses to the questions, the bookmarks will be added in the Buku database.

Do note that in both cases, auto-generated tags will be incorporated in the bookmarks, but you can always change the tags or comments via the `update` option.

Shortening and expanding URLs

Buku can shorten a URL by explicitly supplying it as an argument. You can also use the index of a bookmark you want to shorten. By default, Buku uses the `tiny.im` URL shortening service to shorten URLs.

For example, if you want to shorten the URL of the Wikipedia article `'https://en.wikipedia.org/wiki/Battle_of_Warsaw_(1920)'`, as mentioned earlier, if any special characters are included in the URL, do remember to enclose them within the quotes.

```
$buku --shorten 'https://en.wikipedia.org/wiki/Battle_of_Warsaw_(1920)'
```

The above method will work if you supply the index number of a bookmark instead of the URL.

In the same way, you can expand the URL by using the `--expand` option and supplying the `tiny.im` URL as an argument:

```
$buku --expand http://tiny.im/x000us
```



By: Magimai Prakash

The author has a B.E. degree in computer science. As he is deeply interested in Linux, he spends most of his leisure time exploring open source.