

A sample execution output is shown below for reference:

```
$ ansible-playbook -i inventory/kvm/inventory playbooks/
configuration/elovation.yml --tags rbenv -K
SUDO password:

PLAY [Install dependencies] *****
*****

TASK [Gathering Facts] *****
*****
ok: [ubuntu]

PLAY [Build rbenv] *****
*****

TASK [Gathering Facts] *****
*****
ok: [ubuntu]

TASK [Get rbenv] *****
*****
ok: [ubuntu]

TASK [Build rbenv] *****
*****
changed: [ubuntu]

TASK [Set rbenv PATH] *****
*****
ok: [ubuntu]

TASK [rbenv init] *****
*****
ok: [ubuntu]

PLAY [Build ruby] *****
*****

TASK [Gathering Facts] *****
*****
ok: [ubuntu]

PLAY [Postgresql] *****
*****

TASK [Gathering Facts] *****
*****
ok: [ubuntu]

PLAY [Elovation] *****
*****
TASK [Gathering Facts] *****
*****
```

```
*****
ok: [ubuntu]

PLAY RECAP *****
*****
ubuntu                : ok=9   changed=1
unreachable=0         failed=0
```

Ruby

Ruby-build is a command line utility to install Ruby. Its repository needs to be cloned into the Rbenv plugins folder. Ruby 2.4.0 is then installed using the *rbenv* command, and the same is set as the default global Ruby version in the following playbook:

```
- name: Build ruby
  hosts: ubuntu
  tags: [ruby]

  vars:
    rbenv_root: "/home/{{ ansible_user }}/rbenv"

  tasks:
    - name: Create rbenv plugins
      shell: $SHELL -lc "mkdir -p {{ rbenv_root }}/plugins"

    - name: Get ruby-build
      git:
        repo: 'https://github.com/rbenv/ruby-build.git'
        dest: "{{ rbenv_root }}/plugins/ruby-build"

    - name: Install Ruby 2.4.0
      shell: $SHELL -lc "{{ rbenv_root }}/bin/rbenv install
2.4.0"

    - name: Set Ruby 2.4.0 as Global
      shell: $SHELL -lc "{{ rbenv_root }}/bin/rbenv global
2.4.0"
```

The above playbook can be invoked with the 'ruby' tags option as shown below:

```
$ ansible-playbook -i inventory/kvm/inventory playbooks/
configuration/elovation.yml --tags ruby -vv -K
```

PostgreSQL

Elovation uses the PostgreSQL database, by default, as its backend data store. After updating the APT software package repository, we can install the PostgreSQL server and a few other dependencies. The PostgreSQL database server is started, and the Ansible playbook waits for the database to listen on Port 5432. A separate application user account is created in the database. Although we hard-coded the password in this example, in production, it is recommended that you