

use Vault to encrypt and decrypt the passwords with Ansible. The local authentication is changed from *peer* to *md5* in the PostgreSQL *pg_hba.conf* configuration file, and the database is restarted. The Ansible playbook again waits for the server to listen on Port 5432, as shown below:

```
- name: PostgreSQL
  hosts: ubuntu
  become: yes
  become_method: sudo
  tags: [postgresql]

tasks:
  - name: Update the software package repository
    apt:
      update_cache: yes

  - name: Install dependencies
    package:
      name: "{{ item }}"
      state: latest
    with_items:
      - python3-psycopg2
      - postgresql
      - postgresql-contrib
      - libpq-dev

  - name: Start database server
    systemd:
      name: postgresql
      state: started

  - wait_for:
      port: 5432

  - name: Create application user
    shell: sudo -u postgres createuser -s pguser

  - name: Set password for application user
    shell: sudo -u postgres psql -c "ALTER USER pguser WITH
password 'pguser123'"

  - name: Replace peer auth
    lineinfile:
      path: /etc/postgresql/9.5/main/pg_hba.conf
      regexp: '^local all al
1 peer'
      line: 'local all al
md5'

  - name: Restart database server
    systemd:
      name: postgresql
      state: restarted
```

```
- wait_for:
  port: 5432
```

The above playbook to install and configure the PostgreSQL database server can be run as shown below:

```
$ ansible-playbook -i inventory/kvm/inventory playbooks/
configuration/elovation.yml --tags postgresql -vv -K
```

Elovation

The final step is to set up the Elovation Ruby on Rails application. The bundler software is used to track gems and the versions required by the Rails application. It is installed first and then the Elovation repository is cloned to the HOME folder. The *config/database.yml* file is created and the database credentials are updated. The *bundle install* command is executed to fetch and install the required gems for the application. The database is created for the application and the migrations are executed to create the necessary tables. The entire playbook to set up Elovation is as follows:

```
- name: Elovation
  hosts: ubuntu
  tags: [elovation]

vars:
  rbenv_root: "/home/{{ ansible_user }}/rbenv"

tasks:
  - name: Install bundler
    shell: "{{ rbenv_root }}/shims/gem install bundler"

  - name: Get elovation
    git:
      repo: 'https://github.com/elovation/elovation.git'
      dest: "/home/{{ ansible_user }}/elovation"

  - name: Create database.yml
    copy:
      src: "/home/{{ ansible_user }}/elovation/config/
database.yml.example"
      dest: "/home/{{ ansible_user }}/elovation/config/
database.yml"
      remote_src: yes

  - name: Add database credentials for development database
    lineinfile:
      path: "/home/{{ ansible_user }}/elovation/config/
database.yml"
      insertafter: " database: elovation_development"
      line: " username: pguser\n password: pguser123"

  - name: Add database credentials for test database
    lineinfile:
```