

```
tasks:
- name: Update the software package repository
  apt:
    update_cache: yes

- name: Install monit
  package:
    name: "{{ item }}"
    state: latest
  with_items:
    - net-tools
    - monit

- name: Start monit service
  systemd:
    name: monit.service
    state: started
```

The above playbook can be invoked using the following command:

```
$ ansible-playbook -i inventory/kvm/inventory playbooks/
configuration/monit.yml --tags install -vv -K
```

The `-vv` represents the verbosity in the Ansible output. You can use up to four ‘v’s for a more detailed output. The `-K` option prompts for the *sudo* password for the Debian user account.

Web interface

Monit software provides a Web interface that listens on port 2812. The default configuration file for Monit is located at `/etc/monit/monitrc`. The Web UI port needs to be enabled with basic login credentials. After making changes to the configuration file, the service needs to be restarted. The Ansible playbook to enable the Monit’s Web interface is as follows:

```
- name: Configure UI
  hosts: debian
  become: yes
  become_method: sudo
  gather_facts: true
  tags: [ui]

tasks:
- lineinfile:
    path: /etc/monit/monitrc
    regexp: 'httpd port 2812'
    line: 'set httpd port 2812 and'

- lineinfile:
    path: /etc/monit/monitrc
    regexp: '#    allow admin:monit'
```

```
    line: '    allow admin:monit'

- name: Restart monit service
  systemd:
    name: monit.service
    state: restarted

- wait_for:
    port: 2812
```

The execution of the above playbook to enable the Web interface is shown below:

```
$ ansible-playbook -i inventory/kvm/inventory playbooks/
configuration/monit.yml --tags ui -K
SUDO password:

PLAY [Install Monit] *****
TASK [Gathering Facts] *****
ok: [debian]

PLAY [Configure UI] *****

TASK [Gathering Facts] *****
ok: [debian]

TASK [lineinfile] *****
changed: [debian]

TASK [lineinfile] *****
changed: [debian]

TASK [Restart monit service] *****
changed: [debian]

TASK [wait_for] *****
ok: [debian]

PLAY [Configure ssh monitoring] *****

TASK [Gathering Facts] *****
ok: [debian]

PLAY [Configure ssh monitoring] *****

TASK [Gathering Facts] *****
ok: [debian]

PLAY RECAP *****
debian                : ok=8    changed=3
unreachable=0        failed=0
```

You can use the `netstat` command to verify that Monit is listening on port 2812 as shown below: