

```
$ netstat -na | grep :2812
tcp        0      0 0.0.0.0:2812          0.0.0.0:*
LISTEN
tcp6       0      0 :::2812              :::*
LISTEN
```

The syntax validation of the Monit configuration file can be checked using the following command:

```
$ sudo monit -t
Control file syntax OK
```

The status of the Monit service can be verified as indicated below:

```
$ sudo monit status
Monit 5.20.0 uptime: 2m

System 'debian'
  status          Running
  monitoring status Monitored
  monitoring mode  active
  on reboot       start
  load average    [0.00] [0.02] [0.00]
  cpu             0.4%us 0.3%sy 0.0%wa
  memory usage    45.5 MB [4.6%]
  swap usage      0 B [0.0%]
  uptime          56m
  boot time       Mon, 09 Jul 2018 15:03:06
  data collected  Mon, 09 Jul 2018 15:57:42
```

A summary report of the Monit service can also be printed in the console output as follows:

```
$ sudo monit summary
Monit 5.20.0 uptime: 4m
```

Service Name	Status	Type
debian	Running	System

The status of the Monit service can also be checked from the command line using `systemctl`, as shown below:

```
$ sudo systemctl status monit
[sudo] password for debian:

● monit.service - LSB: service and resource monitoring daemon
```

```
Loaded: loaded (/etc/init.d/monit; generated; vendor
preset: enabled)
Active: active (running) since Mon 2018-07-09 15:55:42
IST; 1min 21s ago
Docs: man:systemd-sysv-generator(8)
Process: 2293 ExecStop=/etc/init.d/monit stop (code=exited,
status=0/SUCCESS)
Process: 2298 ExecStart=/etc/init.d/monit start
(code=exited, status=0/SUCCESS)
Tasks: 2 (limit: 4915)
CGroup: /system.slice/monit.service
└─2305 /usr/bin/monit -c /etc/monit/monitrc
```

```
Jul 09 15:55:42 debian systemd[1]: Stopped LSB: service and
resource monitoring daemon.
Jul 09 15:55:42 debian systemd[1]: Starting LSB: service and
resource monitoring daemon...
Jul 09 15:55:42 debian monit[2298]: Starting daemon monitor:
monit.
Jul 09 15:55:42 debian systemd[1]: Started LSB: service and
resource monitoring daemon.
```

You can now open the URL <http://192.168.122.197:2812> in a browser on the host system to see the default Monit home page, as shown in Figure 1.

When you click on 'debian' under the *System* column, a more detailed status output is made available, as shown in Figure 2.

System	Status	Load	CPU	Memory	Swap
debian	Running	0.00 [0.01] [0.00]	0.0%us, 0.0%sy, 0.0%wa	4.6% [45.5 MB]	0.0% [0 B]

Figure 1: Monit Web UI

Parameter	Value
Name	debian
Status	Running
Monitoring status	Monitored
Monitoring mode	active
On reboot	start
Load average	[0.00] [0.01] [0.00]
Cpu	0.0%us 0.0%sy 0.0%wa
Memory usage	45.6 MB [4.6%]
Swap usage	0 B [0.0%]
Uptime	57m
Boot time	Mon, 09 Jul 2018 15:03:06
Data collected	Mon, 09 Jul 2018 15:59:42

Figure 2: Monit Web UI status

SSH

We can now set up Monit to monitor the SSH daemon running inside the VM. A check block for SSH needs to be added to the Monit configuration file and the service needs to be restarted. The Ansible playbook with the required SSH monitoring configuration is given below: