

Get the path and mode from *rules.txt*:

```
file_t = open(file_name, 'r')
path=file_t.readline()
mode = file_t.readline()
mode = mode.strip("\n").lower()
path1 = path.strip("\n")
```

The following function returns a dictionary that contains the rules. The dictionary's keys behave as extensions of the files, and values act as moved paths, respectively.

```
def rules():
    dict1 = {}
    for each in file_t:
        each = each.strip("\n")
        if each.split(":",1)[0]:
            file_ext,dest_path = each.
split(":",1)
            file_ext = file_ext.strip()
            dest_path = dest_path.
strip()
            dict1[file_ext]=dest_path
    return dict1
```

The following function takes a list of files, and moves the files to their respective folders:

```
def file_move(files_list):
    for file in files_list :
        if "." in file:
            ext = file.rsplit(".",1)[1]
            ext= ext.strip()
            if ext in dict1:
                dst = dict1[ext]
                try:
                    print file
                    shutil.move(file,
dst)
                except Exception as e :
                    print e
```

The following function is used when a simple mode is selected:

```
def single_dir(path1):
    os.chdir(path1)
    files = os.listdir(".")
    file_move(files)
```

The following function is used

when a recursive mode is selected:

```
def rec_dirs(path1):
    for root, dirs,
files in os.walk(path1,
topdown=True, onerror=None,
followlinks=False):
        #print files
        os.chdir(root)
        file_move(files)
        print "files are
moved"

dict1 = rules()

if mode == 'r':
    rec_dirs(path1)
else:
    single_dir(path1)
```

Running the program

So, the program is ready. Now let us convert the Python program into an .exe file.

In order to do this, use the installer shown in Figure 1. After conversion, it will make a directory called *class1\dist*, as shown in Figure 2. Get the *class1.exe* files from the directory *class1\dist* and put them in the Windows folder. Before doing that, you can rename the *exe* file. I am calling it *cfr.exe*. In this way, *cfr.exe* is added to the system path. *cfr.exe* works like a DOS command.

In order to run the program, use Windows' *run* facility, as shown in Figure 3.

After a successful run, check the folders as specified in the *rules.txt*. If the folders do not exist, then the program automatically creates the folders. 

By: Mohit

The author is a certified ethical hacker and EC Council certified security analyst. He has a master's degree in computer science from Thapar University. You can contact him at mohitraj.cs@gmail.com and <https://www.linkedin.com/in/mohit-990a852a/>.




Figure 1: Converting the Python program into an .exe file




Figure 2: .exe. files




Figure 3: Run the program



Figure 4: Folders are created and files are moved