

From now on, you can log into host B as User b from host A as User a without a password:

```
a@A:~> ssh b@B
```

—Ashay Shirwadkar, ashayshirwadkar12@gmail.com



Performance analysis of code

In order to check the performance of the code you have written, you can use a simple tool called 'perf'. Just run the following command:

```
$sudo apt-get install linux-tools-common linux-tools-generic
```

The above command will install the 'perf' tool on Ubuntu or a similar operating system.

```
$perf list
```

The above command gives the list of all the information that can be got by running 'perf'.

For example, to analyse the performance of a C program and if you want to know the number of cache-misses, the command is as follows:

```
$perf stat -e cache-misses ./a.out
```

If you want to use more than one command at a time, give the following command:

```
$perf stat -e cache-misses,cache-references ./a.out
```

—Gunasekar Duraisamy, dg.gunasekar@gmail.com



Create a QR code from the command line

QR code (abbreviated from Quick Response Code) is a type of matrix bar code (or two-dimensional bar code) first designed for the automotive industry. There are many online websites that help you create a QR code of your choice. Here is a method that helps generate QR codes for a string or URL using the Linux command line:




Figure 1: Generated QR code

Secho "Tips and Tricks" | curl -F=@ qrencode.de

To generate the QR code for a domain, use the following code:

```
Secho "http://opensourceforu.com" | curl -F=@<img alt="QR code" data-bbox="500 175 570 225" -> qrencode.de
```



Note: You need a working Internet connection on your computer.

—Remin Raphael, remin13@gmail.com



Replace all occurrences of a string with a new line

Often, we might need to replace all occurrences of a string with a new line in a file. We can use the 'sed' command for this:

```
$sed 's/@@/@/g' file1.txt > file2.txt
```

The above command replaces the string '@@' in 'file1.txt' with a new line character and writes the modified lines to 'file2.txt'.

sed is a very powerful tool; you can read its manual for more details.

—Nagaraju Dhulipalla, nagarajunice@gmail.com



Git: Know about modified files in changeset

Running the plain old 'git log' spews out a whole lot of details about each commit. How about extracting just the name of the files (with their path relative to the root of the Git repository)? Here is a handy command for that:

```
git log -m -l --name-only --pretty="format:" HEAD
```

Changing the HEAD to a different SHA1 commit ID will fetch the names of the files only. This can come in handy while tooling the CI environment.



Note: This will return empty on merge commits.

—Ramanathan M, rus.cahimb@gmail.com



Share Your Open Source Recipes!

The joy of using open source software is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in OSFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.opensourceforu.com. The sender of each published tip will get a T-shirt.