

```

- { regexp: 'root_password_sha2 =',
  replace: 'root_password_sha2 = eabb9bb2efa089223
d4f54d55bf2333ebf04a29094bf00753536d7488629399'}
- { regexp: '#web_enable = false', replace: 'web_
enable = true' }
- { regexp: '#web_listen_uri =
http://127.0.0.1:9000/', replace: 'web_listen_uri = http://{{
ansible_default_ipv4.address }}:9000/' }
- { regexp: 'rest_listen_uri = http://127.0.0.1:9000/
api/', replace: 'rest_listen_uri = http://{{ ansible_default_
ipv4.address }}:9000/api/' }

- name: Start graylog service
  service:
    name: graylog-server.service
    state: started

```

The above playbook can be run using the following command:

```
$ ansible-playbook -i inventory/kvm/inventory playbooks/
configuration/graylog.yml --tags graylog -K
```

Web interface

You can now open the URL <http://192.168.122.25:9000> in a browser on the host system to see the default Graylog login page as shown in Figure 1.

Figure 1: Graylog login page

The user name is 'admin' and the password is 'osfy'. You will then be taken to the Graylog home page as shown in Figure 2.

Figure 2: Graylog home page

The guest VM is a single node, and hence if you traverse to *System -> Nodes*, you will see this node information as illustrated in Figure 3.

Figure 3: Graylog node activated

You can now test the Graylog installation by adding a data source as input by traversing *System -> Input* in the Web interface. The 'random HTTP message generator' is used as a local input, as shown in Figure 4.

Figure 4: Random HTTP message generator