

Figure 5: Graylog input random HTTP message generator

The newly created input source is now running and visible as a local input in the Web page as shown in Figure 5.

After a few minutes, you can observe the created messages in the *Search* link as shown in Figure 6.

Uninstalling Graylog

An Ansible playbook to stop the different services, and to uninstall Graylog and its dependency software packages, is given below for reference:

```
---
- name: Uninstall Graylog
  hosts: ubuntu
  become: yes
  become_method: sudo
  gather_facts: true
  tags: [uninstall]

tasks:
  - name: Stop the graylog service
    service:
      name: graylog-server.service
      state: stopped

  - name: Uninstall graylog server
    package:
      name: graylog-server
      state: absent

  - name: Stop the Elasticsearch server
    service:
      name: elasticsearch.service
      state: stopped

  - name: Uninstall Elasticsearch
    package:
```




Figure 6: Graylog random HTTP messages

```
name: elasticsearch
state: absent
```

- name: Stop the MongoDB server
 service:
 name: mongodb
 state: stopped
- name: Uninstall MongoDB
 package:
 name: mongodb-server
 state: absent
- name: Uninstall pre-requisites
 package:
 name: "{{ item }}"
 state: absent
 with_items:
 - pwgen
 - uuid-runtime
 - openjdk-8-jre-headless
 - apt-transport-https

The above playbook can be invoked using:

```
$ ansible-playbook -i inventory/kvm/inventory playbooks/
admin/uninstall-graylog.yml -K
```



By: Shakthi Kannan

The author is a free software enthusiast and blogs at shakthimaan.com.