

```
ionice = idle
```

Bakthat

Bakthat is a command line tool with the functionalities of cloud based backups. It has excellent features to compress, encrypt and upload the files with a higher degree of integrity and security. Bakthat has many features of data backup with security, including compression with tarfiles, encryption using BeeFish, uploading of data to S3 and Gracier, local backups to the SQLite database, sync based backups and many others.

Installation is as follows:

```
$ pip install bakthat
```

For source based installation, give the following commands:

```
$ git clone https://github.com/tsileo/bakthat.git
$ cd bakthat
$ sudo python setup.py install
```

For configuration with the options of security and cloud setup, give the command:

```
$ bakthat configure
```

Usage is as follows:

```
$ bakthat backup mydirectory
```

To set up a password, give the following command:

```
$ BAKTHAT_PASSWORD=mysecuritypassword bakthat mybackup
mydocument
```

You can restore the backup as follows:

```
$ bakthat restore mybackup
```

```
$ bakthat restore mybackup.tgz.enc
```

For backing up a single file, type:

```
$ bakthat backup /home/mylocation/myfile.txt
```

To back up to Glacier on the cloud, type:

```
$ bakthat backup myfile -d glacier
```

To disable the password prompt, give the following command:

```
$ bakthat mybackup mymyfile --prompt no
```

BorgBackup

BorgBackup (or just Borg, for short) refers to a deduplicating backup tool developed in Python, which can be used in software frameworks or independently. It provides an effective way for secured backup and recovery of data.

The key features of BorgBackup include the following:

- Space efficiency
- Higher speed and minimum delays
- Data encryption using 256-bit AES
- Dynamic compression
- Off-site backups
- Backups can be mounted as a file system
- Compatible with multiple platforms

The commands that need to be given in different distributions to install BorgBackup are given below.

Distribution	Command
Ubuntu	<i>sudo apt-get install borgbackup</i>
Arch Linux	<i>pacman -S borg</i>
Debian	<i>apt install borgbackup</i>
Gentoo	<i>emerge borgbackup</i>
GNU Guix	<i>guix package --install borg</i>
Fedora/RHEL	<i>dnf install borgbackup</i>
FreeBSD	<i>cd /usr/ports/archivers/py-borgbackup && make install clean</i>
Magelia	<i>urpmi borgbackup</i>
NetBSD	<i>pkg_add py-borgbackup</i>
OpenBSD	<i>pkg_add borgbackup</i>
OpenIndiana	<i>pkg install borg</i>
openSUSE	<i>zypper in borgbackup</i>
OS X	<i>brew cask install borgbackup</i>
Raspbian	<i>apt install borgbackup</i>

To initialise a new backup repository, use the following command:

```
$ borg init -e repokey /PathRepository
```

To create a backup archive, use the command given below:

```
$ borg create /PathRepository::Saturday1 ~/MyDocuments
```

For another backup with deduplication, use the following code:

```
$ borg create -v --stats /path/to/repo::Saturday2 ~/Documents
-----
Archive name: MyArchive
```