

If you place the cursor before 'grep' and press *Ctrl + u*, it results in the following output:

```
grep python
```

...while *Ctrl + k* results in the following:

```
ps -ef |
```

—Uma Maheswari P.,
umamaheswari539@gmail.com



Creating a Linux shell command alias

To create the alias, use the *alias* command. It can be useful if you want to create a 'shortcut' to a command.

The format is as follows:

```
$alias name='command'
```

For example, if we want to alias the 'rm' command to *delete*, use the following command:

```
$alias delete='rm'
```

If you want to list all the alias commands for your system, then just run the following command on the terminal:

```
$alias
```

To remove the *alias* command, just run the command given below:

```
$unalias delete
```

—Gunasekar Duraisamy, dg.gunasekar@gmail.com



Find commits made by a particular author in Git

We can list all the commits from the Git repository using the 'git log' command. However, this is not efficient when we need to find out commits made by a particular author. Git provides the '--author' flag, which can be used for this purpose.

If we want to find out commits made by author 'Jarvis', then execute the following command in the Git repository:

```
$ git log --author='Jarvis'
```

This flag also accepts regular expressions, which allow us to perform advanced search.

—Narendra K., narendra0002017@gmail.com



Resize the screen from the command line

The 'xrandr' utility can help us set or change the screen size from the command line. Xrandr is used to

set the size, orientation and/or reflection of the outputs for a screen. It can also set the screen size.

If invoked without any option, it will dump the state of the outputs, showing the existing modes for each of them, with a '+' after the preferred modes and a '*' after the current mode.

It also displays the list of available resolutions. For instance, the output given below shows the resolution available on the current machine:

```
$ xrandr
```

```
Screen 0: minimum 320 x 200, current 1366 x 768, maximum 8192 x 8192
```

```
eDP-1 connected primary 1366x768+0+0 (normal left inverted right x axis y axis) 309mm x 173mm
```

1366x768	60.07*+	40.04	
1360x768	59.80	59.96	
1024x768	60.04	60.00	
960x720	60.00		
928x696	60.05		
896x672	60.01		
960x600	60.00		
960x540	59.99		
800x600	60.00	60.32	56.25
840x525	60.01	59.88	
800x512	60.17		
700x525	59.98		
640x512	60.02		
720x450	59.89		
640x480	60.00	59.94	
680x384	59.80	59.96	
576x432	60.06		
512x384	60.00		
400x300	60.32	56.34	
320x240	60.05		

```
HDMI-1 disconnected (normal left inverted right x axis y axis)
```

```
DP-1 disconnected (normal left inverted right x axis y axis)
```

The output also shows that the computer has one HDMI and one VGA port that can be used for external display and the supported screen size for the current display.

We can also change the resolution using the following command:

```
$ xrandr --output LVDS --mode 1024x768
```

—Suvesh Kumar, suvesh.kumar@nixtrainer.com



Share Your Open Source Recipes!

The joy of using open source software is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in OSFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.opensourceforu.com. The sender of each published tip will get a T-shirt.