



TIPS & TRICKS



Auto restart Apache after every *.conf* file change

Shown below are the steps to auto restart Apache after every change made to the *.conf* file.

If 'incron' is already installed in your system, then skip Steps 1 and 2.

```
$ sudo apt-get install incron
$ sudo nano /etc/incron.allow
```

Add *<USERNAME>* at the end of this file and save.

```
$ sudo incrontab -e
```

Once the *incrontab* is open in editable mode, add the following line at the end of the content:

```
/etc/apache2/apache2.conf IN_MODIFY /usr/sbin/service
apache2 restart
```

Save and exit the file.

From now on, every change in the */etc/apache2/apache2.conf* file will trigger */usr/sbin/service apache2 restart* to restart the Apache server. You can also use *incron* to perform other useful tasks.

—Swapnil Srivastava, swapnil99@gmail.com



Recovering the MySQL root password

There are so many situations in which you need to recover the root password of your MySQL installation.

To recover the password, first stop the MySQL service, as follows:

```
# /etc/init.d/mysqld stop
```

Add *skip-grant-tables* by editing the *my.cnf* file:

```
# vim /etc/my.cnf
```

After opening the file in any text editor, add *skip-grant-tables* under the *[mysqld]* section. Save and exit the file. Now you can start the MySQL service, as follows:

```
# /etc/init.d/mysqld start
```

Next, you need to log into the MySQL server without any password, as shown below:

```
# mysql
```

Use the following code to reset the password for the 'root' user:

```
mysql> use mysql
mysql> UPDATE user SET password=PASSWORD('new_pass') where
user='root';
```

For flush privileges, use the code shown below:

```
mysql> flush privileges;
mysql> exit
```

Now, revert back to the previous state by stopping the MySQL service, as follows:

```
# /etc/init.d/mysqld stop
```

Edit *my.cnf* and remove *skip-grant-tables*.

After saving the *my.cnf* file, you can start the MySQL service:

```
# /etc/init.d/mysqld start
```

Now you can log in with the new password, using the following command:

```
# mysql -u root -p new_pass
```

—Kishor Gavali, kishorgavali@gmail.com