

```
- "aide_db_result.stat.exists == true"
```

## RHEL-06-000019

The *.rhosts* and */etc/hosts.equiv* files used by the *rsh* daemon can allow unauthorised access to the system. Hence, these should not exist in the file system. The Ansible Stat module is used to check the presence of these files.

```
- name: "RHEL-06-000019 | CAT I | There must be no /etc/
hosts.equiv files"
  stat:
    path: /etc/hosts.equiv
    register: etc_hosts_result

- assert:
  that:
    - "etc_hosts_result.stat.exists == false"

- name: "RHEL-06-000019 | CAT I | There must be no .rhosts
file"
  stat:
    path: ~/.rhosts
    register: rhosts_result

- assert:
  that:
    - "rhosts_result.stat.exists == false"
```

## RHEL-06-000020

The SELinux policy needs to be set to 'Enforcing' in the */etc/selinux/config* file. This setting needs to take effect from the boot time, and it enforces limits on system services.

```
- name: "RHEL-06-000020 | CAT II | The system must use a
Linux Security Module to enforce limits"
  shell: "grep ^SELINUX= /etc/selinux/config"
  register: selinux_result

- assert:
  that:
    - "'enforcing' in selinux_result.stdout"
```

## RHEL-06-000023

The SELinux targeted policy ensures that processes that are targeted run in a confined domain, and those that are not, run in an unconfined domain. The SELINUXTYPE variable needs to be set to 'targeted' in */etc/selinux/config* for this setting to take effect.

```
- name: "RHEL-06-000023 | CAT III | The system must use a
Linux Security Module to limit the privileges"

  shell: "grep ^SELINUXTYPE= /etc/selinux/config"
  register: selinux_type_result
```

```
- assert:
  that:
    - "'targeted' in selinux_type_result.stdout"
```

## RHEL-06-000032

We need to ensure that there is only one root user in the system. The */etc/passwd* file can be checked to see that there is only one entry with UID 0.

```
- name: "RHEL-06-000032 | CAT II | The root account must be
the only account having UID 0"

  shell: "awk -F: '($3 == 0) {print}' /etc/passwd"
  register: root_account_result

- assert:
  that:
    - "root_account_result.stdout_lines | length == 1"
```

The entire playbook invocation and run to check the above STIG-IDs is shown below:

```
$ ansible-playbook -i inventory/kvm/inventory playbooks/
configuration/stig.yml

PLAY [STIG]*****

TASK [Gathering Facts] *****
ok: [centos]

TASK [RHEL-06-000005 | CAT II | The audit system must alert
designated staff members] *****

changed: [centos]

TASK [assert] *****
ok: [centos] => {
  "changed": false,
  "msg": "All assertions passed"
}

TASK [RHEL-06-000008 | CAT I | Vendor-provided cryptographic
certificates must be installed]*****

changed: [centos]

TASK [assert] *****
ok: [centos] => {
  "changed": false,
  "msg": "All assertions passed"
}

TASK [RHEL-06-000011 | CAT II | System security patches and
updates must be installed] *****
```